

DRAWING MADE IN THIRD ANGLE PROJECTION


MOD 40

LOC AJ

DIST 16

REVISIONS

P	REV	DESCRIPTION	DATE	APPROVED
1	D	REV & REDWN	7-15-83	5/DA/83
2	E	ADD PIN 22000-1 PER AJ-3009	3/1/88	5/DA/88



1. 1.80 MIN DIA HOLE REQ'D FOR CONTACT TO FEED THROUGH P.C. BOARD.

2. FOR USE WITH: RG-178/U DBL BRAID, 176/U, MALCO * 250-3908-0000, & TEASOLITE * 30850/817-1.

3. CRIMPING TOOL: 220215-1.

4. SEE LS. 2923.

RECOMMENDED STRIP LENGTH

5. ITEM 3 IS USED TO STABILIZE CONTACT IN THE HOUSING CAVITY; OTHERWISE DISCARD.

ITEM	QTY	DESCRIPTION	PART NO
3	1	SPRING, ALIGNMENT	222000-1
2	1	SOCKET ASSY, RTANG	227626-1
1	1	FERRULE	227622-2

USE UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON:
DECIMALS ± .005
ANGLES ± .5°

MATERIAL

FINISH

CONTRACT NO

DR

CHK

APPD

APPD

DESN APPD

OTHER APPD

AMP

AMP INCORPORATED
Harrisburg, Pa. 17105

NAME

CONNECTOR, COAXIAL, MULTIPLE, RF,
CONTACT, SOCKET, RTANG, C

SIZE

A

FSCM NO

00779

DRAWING NO

227606-1

SCALE AITS

SHEET

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[227606-1](#)