




ABSOLUTE MAXIMUM RATINGS AT 25° C AMBIENT	R/G BI-COLOR		UNITS
	GREEN	RED	
POWER DISSIPATION	100	100	mW
CONTINUOUS FORWARD CURRENT	30	30	mA
DERATE LINEARLY FROM 50° C	0.4	0.4	mA / °C
PEAK FORWARD CURRENT (1/10 DUTY CYCLE, 0.1 ms PULSE WIDTH)	120	120	mA
REVERSE VOLTAGE	5	5	V
LEAD SOLDERING TEMPERATURE, 5 SEC., 1/16 FROM BODY	260		°C
OPERATING TEMPERATURE	-55 TO +100		°C
STORAGE TEMPERATURE	-55 TO +100		°C


REV.	ECN NO.	REVISIONS	DRN.	CKD.	APP.	DATE
A	—	NEW RELEASE	DC			



RECOMMENDED P.C.B. HOLE PATTERN

OPERATING CHARACTERISTICS AT 25° C AMBIENT

LED CHARACTERISTICS	COLOR	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
LUMINOUS INTENSITY	GREEN RED	1.7 1.7	5.6 5.6		mcd	$I_F = 20 \text{ mA}$
FORWARD VOLTAGE	GREEN RED		2.1 2.0	2.8	V	$I_F = 20 \text{ mA}$
REVERSE CURRENT (I_R)	GREEN RED			100	μA	$V_R = 5\text{V}$
PEAK WAVELENGTH (λ_p)	GREEN RED		565 630		nm	MEASUREMENT @ PEAK
DOMINANT WAVELENGTH (λ_d)	GREEN RED		569 621		nm	MEASURED ON EXELTRON 2001
VIEWING ANGLE ($2\theta_{1/2}$)	GREEN RED		140		deg.	
CAPACITANCE	GREEN RED		35 20		pF	$V_R = 0 \text{ V}, f = 1 \text{ MHz}$



NOTE:
I. DIALIGHT PART NO. 566-0706-801

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE 5:1	DRAWING NUMBER	REV
ALL DIM'S IN: INCHES	C-16745	A
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE	
FRACTIONS: $\pm 1/64$	RECTANGULAR RIGHT ANGLE R/G CBI	
DECIMALS (.XX): $\pm .020$	MATERIAL	
DECIMALS (.XXX): $\pm .015$		
ANGLES: $\pm 3^\circ$		
FINISH:	Dialight	1913 ATLANTIC AVE. MANASQUAN, N.J. 08736
FSCM 83330	SHEET OF	FAMILY TABLE:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Dialight:

566-0706-801F