


STRIPPING DIMENSION (c)



Part-no. as per finish			
(c) GOLD FLASH over NICKEL (d)	min. 20µin HARD GOLD over min. 50µin NICKEL	min. 30µin HARD GOLD over min. 50µin NICKEL	min. 50µin HARD GOLD over min. 50µin NICKEL
162A18719X	162B18719X	162C18719X	162J18719X

- (c) **NOTES:**
1. Material: Copper alloy
  2. Finish: See table
  3. Temperature range: -55 °C to +125 °C
  4. Rated current: 5 A maximum
  5. Contact resistance: <= 10 mOhm
  6. Crimping: Use crimp tool 360X10329X  
With tool insert 360X20069X  
Selector settings: 7 for AWG 24  
6 for AWG 26  
5 for AWG 28

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND				tolerance		 dim. in mm
				DIN ISO 2768-m		
				date	name	
				drawn	14.02.03	Parei
3 x e	Ä5346	17.09.2014	K.H.	appd.	14.02.03	Kühle
1 x d	Ä 4116	26.09.11	Lehm.	norm		
4 x c	Ä 3698	25.08.10	Lehm.	d-old		
1 x b	Ä 2127	02.12.04	Lehm.			
a	Original					
rev.	description	date	name			

scale:	5:1	
material:	SEE NOTES	
title:	<b>CRIMP SOCKET CONTACT</b> screw machined version accepts cable AWG 28-24	
dwg no:	Inventor 10	DIN-A4
	16K1A886	sh: 1
part no:	SEE TABLE	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[162A18719X](#)