







1. MATERIAL:
BOOT: THERMOPLASTIC ELASTOMER
SEAL: VITON
HOUSING BODY: ZINC DIE CAST, NICKEL PLATED

2. SPECIFICATIONS:
2.1 DEGREE OF PROTECTION: IP67 (MATED CONDITION)
2.2 ROHS COMPLIANT
2.3 CABLE OD RANGE: 17.5~18.5mm

NOTES: UNLESS OTHERWISE SPECIFIED

| ယ |
|-------------------|
| Æ |
| o |
| ⋜ |
| 旦 |
| ŝ |
| 9 |
| SA |
| æ |
| Ë |
| 8 |
| æ |
| Ħ |
| 盟 |
| Θ̈́ |
| Ö |
| \mathbb{E} |
| Ξ |
| 0 |
| $\stackrel{>}{=}$ |
| \prec |
| |

| | Α1 | REV | |
|--|-------------------|-------------|-----------|
| | | ECO | |
| | FIRST RELEASE | DESCRIPTION | REVISIONS |
| | May 15,2015 Drack | DATE | |
| | Drack | ВҮ | |
| | TOMMY | BY APPR | |

| NEXT ASS'Y | | PROCESS SPECIFICATIONS: | | MATERIAL SPECIFICATIONS: | | 3) Note reference = | 2 PL DEC ±0.15 3 PL DEC ±0.08 | 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions +1/6- | UNLESS OTHERWISE SPECIFIED | | QUANTITY | | | | |
|---------------------------|--|-------------------------|---------------------------|--------------------------|--|---------------------|--------------------------------------|---|----------------------------|----------------|------------------|-----------------------|------------|--------|--|
| | | | | TONS: | | | _ | ns +1/64 | VISE SPECIFIED | | PART NUMBER | SEE PART NU | | | |
| MANUFACTURING VARIATIONS. | THIS DRAWING IS SUPPLIED FOR NEODERATION ON U. DESIGN FEATURES. SECRIFICATIONS AND DERFORMANCE DATA SIZE SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL | | CUSTOMER: | | APPROVAL: | ENGINEER: | CHECKED: | Drack Drack | SIGNATURES | MA | UMBER | SEE PART NUMBER CHART | | | |
| | | | | | | | | May 15,2015 | S DATE | MATERIALS LIST | | | | | |
| SCALE: NONE | ω | | | | | | | | | YLS | | | | | |
| NE N | Ç- | | | | | | | | | Sin | \triangleright | | <u>_</u> ; | E E | |
| SHEET 1 OF | MC4FSR-C18.5 | | M40,CORD GRIP,17.5~18.5mm | | 44724 Morley Drive Clinton Township, MI 48036 | | Sine Systems - www.amphenol-sine.com | Amphenol | | IST | DESCRIPTION | | | | |
| | | | | | | | | | | | TEM | | | | |

тпе: М40,CОRD GRIP,175-18.5mm рwe чо: МC4FSR-C18.5 REV. Д1 sH: 1 оF: 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: MC4FSR-C18.5