


1. UL LISTED AND CSA CERTIFIED FOR:
 - A. 600V. MAX. BLDG WIRE
(1000 V. MAX IN SIGNS, FIXTURES & LUMINARIES)
 - B. #14-10 AWG SOLID OR STRANDED
COPPER WIRE WITH THE CT-550
INSTALLATION TOOL.
 - C. #12-10 AWG STRANDED AND NO.12 AWG
SOLID COPPER WIRE WITH THE CT-1550
AND CT-1551 INSTALLATION TOOLS.
 - D. 221°F (105°C) MAX TEMP. RATING
2. MATERIAL:
 - A. STAMPING - .04" (1.02) THK COPPER, TIN PLATED
 - B. HOUSING - NYLON, YELLOW
 - C. SLEEVE - BRASS, TIN PLATED
3. STRIP LENGTH - 9/32 $\pm \frac{1}{32}$ /₀
4. SEE www.panduit.com FOR PART NUMBER
SUFFIX DESIGNATION FOR PACKAGE SIZE.
5. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS



									PANDUIT CORP. TINLEY PARK, ILLINOIS			
									#12-10 BARREL NYLON INSULATED LOCKING FORK, .225 (5.72) MAX. WIRE INSULATION DIAMETER			
09	5/11	SB		REVISED NOTE # 4								
REV	DATE	BY	CHK	DESCRIPTION	ECN	CUST	PM	DRAWN BY DAW	CHK'D LA	SCALE NONE	DRAWING NO. A41292	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[PN10-10LF-L](#) [PN10-6LF-L](#) [PN10-8LF-L](#) [PN10-6LF-D](#) [PN10-10LF-D](#) [PN10-14LF-L](#) [PN10-8LF-D](#) [PN10-14LF-D](#)