
XZCP1865L10

pre-wired connectors XZ - straight female - 1/2"20 UNF - 3 pins - cable PUR 10m

Product availability: Non-Stock - Not normally stocked in distribution facility



Main Commercial Status Commercialised Accessory / separate Cabling accessories part category Accessory / separate Pre-wired connectors part type General purpose Series name Electrical connection Straight female connector 1/2"20 UNF, 3 pins Collar material Metal Status LED Without Cable length 32.81 ft (10 m)

Complementary

Cable connector fixing	Screw-on	
Cable outer diameter	0.2 in (5.2 mm)	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	300 V DC 250 V AC	
[In] rated current	4 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.77 lb(US) (0.35 kg)	

Environment

IP degree of protection	IP67	
Ambient air temperature for operation	23194 °F (-590 °C) (flexing) -31194 °F (-3590 °C) (static)	
Ambient air temperature for storage	-31212 °F (-35100 °C)	

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	00785901389651
Nbr. of units in pkg.	1
Package weight(Lbs)	0.78
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	DE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0649 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCP1865L10