


## Cover profile - A/F 40 METER - 1004940

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Flat-ribbon cover, for covering terminal strips, 2 mm thick, 4 cm wide, an additional requirement are 2 E/UK end brackets and 2 adjustable VAH cover holders. The max. supply length is 100 cm

The illustration shows a combination of versions A/F, A/U, VAH, A/F-HA



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 017918 012298 |
| Weight per Piece (excluding packing) | 125.0 g                                                                                                 |
| Custom tariff number                 | 39206100                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 1 m   |
| Width (a)  | 40 mm |

#### General

|                                        |                  |
|----------------------------------------|------------------|
| Color                                  | transparent      |
| Flammability rating according to UL 94 | V2               |
| Material                               | Polycarbonate PC |

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V2 |
|----------------------------------------|----|

## Cover profile - A/F 40 METER - 1004940

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 23150301 |
| eCl@ss 4.1 | 23150301 |
| eCl@ss 5.0 | 27141143 |
| eCl@ss 5.1 | 27141143 |
| eCl@ss 6.0 | 27379200 |
| eCl@ss 7.0 | 27141143 |
| eCl@ss 8.0 | 27149214 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC002498 |
| ETIM 5.0 | EC002848 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 39121708 |
| UNSPSC 11     | 39121708 |
| UNSPSC 12.01  | 39121708 |
| UNSPSC 13.2   | 39121708 |

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1004940](#)