

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

MAR ,1988.

© COPYRIGHT 1988 By -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

変更

P

LTR

DESCRIPTION

DATE

DWN

APVD

B

REVISED PER ECO-15-002720



02MAR2015

AP

SB

40,60 POS

30,50 POS



DATUM

 ± 0.5
3.15.0
 ± 0.3
7.7

D

B

PITCH
1.27 Xn=A

DATUM

1.27 PITCH

(UPPER)

E

(BELOW)

E




CIRCUIT No.

- 1 USE A P.C.B. WHOSE ARE TREATED WITH SOLDER RESIST.
- 2 SHOW P.C.B LAYOUT FROM ON BOARD SURFACE SIDE.
- 3 NUMBER THE CONTACT IN THE P.C.B OR CONNECTOR CONSECUTIVELY FROM "DATUM" SIDE.

④ HOUSING MATERIAL : P.B.T(UL94V-0) / BLACK

⑤ CONTACT MATERIAL : PHO-BRONZE


⑥ FINISH : NICKEL 0.00127 MIN THK. OVERALL SELECTIVE GOLD 0.00076 MIN. OR 0.0002 MIN. THK ON CONTACT AREA AND TIN 0.001 MIN THK. ON TINE AREA.

E-E
SCALE 5:120,40,60 POS
ON BOARD SIDE

6-	-5	20	9	11.43	15.60	19.20	Au PL. 0.00076 MIN.
6-	-4	60	29	36.83	41.00	44.60	
6-	-3	50	24	30.48	34.65	38.26	
6-	-2	40	19	24.13	28.30	31.90	
6-	-1	30	14	17.78	21.95	25.55	
	-5	20	9	11.43	15.60	19.20	Au PL. 0.0002 MIN.
	-4	60	29	36.83	41.00	44.60	
	-3	50	24	30.48	34.65	38.26	
	-2	40	19	24.13	28.30	31.90	
5174215-1	30	14	17.78	21.95	25.55		
PART NUMBER	POS	n	A	B	D	REMARK	

OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:
一般公差MATERIAL
材料

SEE NOTE ④⑤

FINISH
仕上

SEE NOTE ⑥

DWN 06JUL04

GAVIN ZHANG

CHK 06JUL04

T. KAWAMAE

APVD 06JUL04

I. ENOMOTO

PRODUCT SPEC

製品規格

108-60036

APPLICATION SPEC

取付適用規格

WEIGHT

CUSTOMER DRAWING

STE

TE Connectivity

NAME
名称PLUG ASSY (VERTICAL W/O SCREW HOLE)
AMPLIMITE 050 SERIES I B-TO-B CONN.

SIZE

CAGE CODE

DRAWING NO
番号

RESTRICTED TO

A3

00779

C-5174215

SCALE
尺度 2:1

SHEET

1 OF 1

REV
BGENERAL TOLERANCE
一般公差10 ≥ : ±0.2
30 ≥ > 10: ±0.25
100 ≥ > 30: ±0.3
ANGLES: ±3°

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-5174215-1](#)