# Product data sheet Characteristics

## XZCRV1511041C1

# jumper cable XZ - male straight M12 4-pin - female straight M12 4-pin - PVC 1m

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Jumper cable
Jumper cable end 1	M12 male 4 pins straight connector with screw-on
Jumper cable end 2	M12 female 4 pins straight connector with screw-on

## Complementary

Collar material	Metal	
Cable composition	4 x 0.25 mm²	
Cable length	3.28 ft (1 m)	
Wire insulation material	PVC	
Cable outer diameter	0.18 in (4.6 mm)	
[Ue] rated operational voltage	300 V DC 250 V AC	
[In] rated current	3 A	
Insulation resistance	>= 1000 MOhm	
Resistance across terminals	<= 5000 mOhm	
Product weight	0.15 lb(US) (0.07 kg)	
		$\overline{}$

### **Environment**

IP degree of protection	IP65
Ambient air temperature for operation	-13176 °F (-2580 °C) (static)
Ambient air temperature for storage	-13176 °F (-2580 °C)

### Ordering and shipping details

22483 - MACHINE CABLES
DS3
00785901712336
1
0.13
Non-Stock - Not normally stocked in distribution facility
Υ
DE

#### Contractual warranty

Period 18 months		

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCRV1511041C1