



CAT. NUMBER	A	B	C	ØD	ØE	ØF
UTG1104S (H)	24,3	5	8,65	15	19,5	9/16-24 UNEF
UTG1125S (H)	24,3	5	8,65	19	23,5	11/16-24 UNEF
UTG1128S (H)	24,3	5	8,65	19	23,5	11/16-24 UNEF
UTG11412S (H)	24,3	5	8,65	22,2	27	13/16-20 UNEF
UTG11619S (H)	24,3	5	8,65	25,3	30	15/16-20 UNEF
UTG11823S (H)	24,3	5	8,65	28,5	36,5	1.1/16-18 UNEF
UTG12028S (H)	27	5	12,05	31,7	36,5	1.3/16-18 UNEF
UTG12235S (H)	28	5	12,05	34,9	39,7	1.5/16-18 UNEF
UTG12448S (H)	30,4	5	13,85	38	42,5	1.7/16-18 UNEF

MATERIAL :
 _ BODY : GLASS FILLED POLYESTER UL94-V0 COLOUR BLACK
 _ TRILOK RING : HIGH STRENGTH CuZn ALLOY, NICKEL PLATED

PERFORMANCE CHARACTERISTICS :
 _ OPERATING TEMPERATURE : -55°C TO 125°C
 _ INSULATION RESISTANCE : 5000 MΩ MIN
 _ TEST POTENTIAL : 2000 V EFF

- NOTES :**
- CONNECTOR ACCEPTS #16 STRIP FORMED SOCKET, MACHINED SOCKET AND SUBMINIATURE COAXIAL PIN AND SOCKET CONTACTS
 - CONTACTS TO BE ORDERED SEPARATELY : REFER TO TRIM-TRIO CATALOG
 - FOR LAYOUT IDENTIFICATION SEE BS,C,201458,000
 - FOR WATERPROTECTED VERSION : ADD "H" TO THE CAT. NO. E.G. CAT.NUMBER: UTG1128SH

P/N : SEE TABLE

B	24/02/2015	_ Adding value ØF thread diameter		—
ISS	DATE	Latest modification - by:	COUZY L.	MOD N°
Designed by:		BUEDS M.	Date:07/06/1991	CUSTOMER DRAWING
TITLE	FEMALE RECEPTABLE FREE HANGING			
Scale	1/1	General linear Tolerances: ± 0,2	NPRDS / PROJECT BE150902A	
SOURIAU	WWW.SOURIAU.COM		This document is the property of SOURIAU. It must not be reproduced or communicated without permission.	
FORMAT	SOURIAU DRG N° BSA201458006			SHEET
A2				1/1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Souriau:](#)

[UTG11823SH](#) [UTG116-19S](#) [UTG114-12S](#) [UTG11412SH](#) [UTG1128SH](#) [UTG11823S](#) [UTG116-19SH](#) [UTG1128S](#)
[UTG1103S](#) [UTG1104SH](#) [UTG1104S](#) [UTG12448S](#) [UTG12028S](#)