

Customer Information Sheet

DRAWING No.: M50-90XXX42

SHEET 2 OF 2


IF IN DOUBT - ASK

©

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm



SPECIFICATIONS:

MATERIAL:
MOULDINGS = PBT 30% G/F, UL94V-0, BLACK
CONTACT = PHOSPHOR BRONZE

FINISH:
CONTACTS:
M50-330XX42 = 0.015-0.02µm MIN GOLD ON CONTACTS, 2.54µm MIN 100% TIN ON TAILS, OVER 0.76-2.03µm NICKEL
M50-380XX42 = 0.015-0.02µm MIN GOLD ON CONTACTS, OVER 0.76-2.03µm NICKEL

ELECTRICAL:
CONTACT RESISTANCE = 1.0Ω MAX
WORKING VOLTAGE = 300V DC 10 SECONDS
INSULATION RESISTANCE = 5MΩ MIN

MECHANICAL:
DURABILITY = 100 CYCLES MIN
INSERTION FORCE = 1.0N MAX PER CONTACT
WITHDRAWAL FORCE = 0.14N MIN PER CONTACT

ENVIRONMENTAL:
TEMPERATURE RANGE = -20°C TO +105°C

PACKING:
SEE ERP FOR PACKAGING
FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C029XX (LATEST ISSUE)

ORDER CODE	M50-90XXX42
DIM 'A':	SEE TABLE
No. OF CONTACTS PER ROW:	05, 10, 13, 17, 20, 25

PART No.	DIM 'A'
M50-900XX42	50
M50-901XX42	150
M50-902XX42	300

RA	8	17.03.20	22295
NAME	ISS.	DATE	C/NOTE
APPROVED:		R.ALEXANDER	
CHECKED:		M.PLESTED	
DRAWN:		R.ADDE	
CUSTOMER REF.:			
ASSEMBLY DRG:			

- NOTES:**
- CONNECTORS M50-330XX42 & M50-380XX42, AS WELL AS CABLE, ARE RoHS COMPLIANT.
 - FOR CONNECTOR DETAILS SEE DRAWINGS M50-330XX42 & M50-380XX42.

HARWIN

www.harwin.com
technical@harwin.com

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±1mm
X.X = ±0.50mm
X.XX = ±0.20mm
X.XXX = ±0.01mm
ANGLES = ±5°
UNLESS STATED

MATERIAL:
SEE ABOVE

FINISH:
SEE ABOVE

S/AREA:
mm²

TITLE:
1.27mm PITCH IDC
DIL SOCKET/PLUG
CABLE ASSEMBLY

DRAWING NUMBER:
M50-90XXX42

SHT
2 OF 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Harwin:](#)

[M50-9021742](#) [M50-9012042](#) [M50-9022542](#) [M50-9012542](#) [M50-9021042](#) [M50-9011742](#) [M50-9022042](#) [M50-9011342](#) [M50-9020542](#) [M50-9021342](#) [M50-9011042](#) [M50-9010542](#)