


# Multiple Stud Type Junction Blocks (Non Feed-Thru)


## Series C4559 & C6083



**Dimensions - mm(in)** (Dims. shown are for reference only. Consult factory for latest prints)



Other series available with .750" centers:



(A,B,C Dimensions are the same as C4559)

### Specifications

**Rating:** 30A, 600V  
**Temperature Rating:** 250°F (120°C)  
**Materials:** Black thermoplastic with zinc-plated steel studs  
**Termination:** #10-24 Threaded studs on .750" centers. Studs feature a "dog point" to guide nut onto thread  
**Torque Rating:** 25 in-lbs (2.8N•m) max  
**Mounting Torque Rating:** 24 in-lbs (2.7N•m) max

### Options

**Positions:** 2-16 positions available.

### Features



Numbers and arrows molded on top of barriers indicate terminals.  
**Compliances:** E248514; UL/CSA; CE Certified

Part No.	A	B	C
C4559-2	3.00 (76.2)	2.25 (57.1)	0.75 (19.0)
C4559-3	3.75 (95.2)	3.00 (76.2)	1.50 (38.1)
C4559-4	4.50 (114.3)	3.75 (95.2)	2.25 (57.1)
C4559-5	5.25 (133.3)	4.50 (114.3)	3.00 (76.2)
C4559-6	6.00 (152.4)	5.25 (133.3)	3.75 (95.2)
C4559-7	6.75 (171.4)	6.00 (152.4)	4.50 (114.3)
C4559-8	7.50 (190.5)	6.75 (171.4)	5.25 (133.3)
C4559-9	8.25 (209.5)	7.50 (190.5)	6.00 (152.4)
C4559-10	9.00 (228.6)	8.25 (209.5)	6.75 (171.4)
C4559-11	9.75 (247.6)	9.00 (228.6)	7.50 (190.5)
C4559-12	10.50 (266.7)	9.75 (247.6)	8.25 (209.5)
C4559-13	11.25 (285.7)	10.50 (266.7)	9.00 (228.6)
C4559-14	12.00 (308.4)	11.25 (285.7)	9.75 (247.6)
C4559-15	12.75 (323.8)	12.00 (308.4)	10.50 (266.7)
C4559-16	13.50 (342.9)	12.75 (323.8)	11.25 (285.7)

## Series C5237 & JB1032



**Dimensions - in** (Dims. shown are for reference only. Consult factory for latest prints)



(A,B,C Dimensions are the same as C5237)

### Specifications

**Rating:** UL: 30A, 300V; CSA: 30A, 600V  
**Temperature Rating:** 250°F (120°C)  
**Materials:** Black thermoplastic with yellow zinc-plated brass studs  
**Termination:** #10-32 Threaded studs on .625" centers. Studs feature a "dog point" to guide nut onto thread  
**Torque Rating:** 25 in-lbs (2.8N•m) max  
**Mounting Torque Rating:** 24 in-lbs (2.7N•m) max

### Options

**Positions:** 1-15 positions available

### Features

Numbers and arrows molded on top of barriers indicate terminals.  
**Compliances:** UL/CSA; CE Certified

Part No.	A	B	C
C5237-1	2.00 (50.8)	1.25 (31.7)	-
C5237-2	2.62 (66.7)	1.87 (47.5)	.625 (15.9)
C5237-3	3.25 (82.5)	2.50 (63.4)	1.25 (31.7)
C5237-4	3.87 (98.4)	3.12 (79.4)	1.87 (47.5)
C5237-5	4.50 (114.3)	3.75 (95.2)	2.50 (63.4)
C5237-6	5.12 (130.8)	4.37 (111.1)	3.12 (79.4)
C5237-7	5.75 (146.0)	5.00 (127.0)	3.75 (95.2)
C5237-8	6.37 (161.9)	5.62 (142.9)	4.37 (111.1)
C5237-9	7.00 (177.8)	6.25 (158.7)	5.00 (127.0)
C5237-10	7.62 (193.7)	6.87 (174.6)	5.62 (142.9)
C5237-11	8.25 (209.5)	7.50 (190.5)	6.25 (158.7)
C5237-12	8.87 (225.4)	8.12 (206.4)	6.87 (174.6)
C5237-13	9.50 (241.3)	8.75 (222.2)	7.50 (190.5)
C5237-14	10.12 (257.2)	9.37 (238.1)	8.12 (206.4)
C5237-15	10.75 (273.0)	10.00 (254.0)	8.75 (222.2)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eaton:](#)

[C4559-5](#) [C4559-12](#) [C4559-9](#) [C4559-14](#) [C5237-4](#) [C4559-3](#) [C4559-7](#) [C5237-2](#)