



Sechskantschraubendreher SW5  
hexagonal driver

Beispielhafte Darstellung: 09 11 001 2752  
exemplary drawing: 09 11 001 2752

Absolierlänge: 19<sup>+1</sup> mm  
stripping length: 19<sup>+1</sup> mm

Isolationdurchmesser: max. 19,5 mm  
insulation diameter: max. 19,5 mm

A	(mm <sup>2</sup> )	AWG	Nm	All Dimensions in mm Original Size DIN A 4			Techn. Character.			Nicht tolerierte Masse/ Free size tolerances		
				Mod.	Dat.	Name	Detail.	Dat.	Name	Massstab/ Scale	Han 1HC-F-AX Buchsenträger, axialschraub female insert, axial screw	
09 11 001 2752	95-120	4/0-5/0	12-14				Detail.	29.07.98	SPER	1:1		TB 09 11 001 27..
09 11 001 2751	35-70	2-2/0	6-10	29679	05.07.01	Gö	Insp.		OLE			
09 11 001 2750	20-35	4-2	6	24849	02.12.98	PL	Stand.					
Bestell Nr / Part No	Litzenquerschnitt / Wire gauge		Anzugsmoment / Tightening torque	Mod.	Dat.	Name	HARTING KGaA D-32339 ESPELKAMP			HARTING	Sub.	Blatt/ page

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09110012751](#)