

AMP 1281 (7/69)

APPLICATOR PARTS LIST

TYPE

LENGTHWISE

RING
AMPLINAR
STUD RETAININGAMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA	TERMINALS
1	WIRE CRIMPER	1	456408-6	42	BENDING TOOL	1	458961-4	TO APPLY TERMINAL	505017
2	INS. CRIMPER			43				MAG	
3	ANVIL	1	2-473405-5	44				WIRE SIZE	CRIMP HEIGHT
4	ANVIL SPACER			45				20	.054
5	SHEAR BLADE	1	375307	46				18	.057
6	REAR SHEAR PLATE	1	385013-4	47				16	.062
7	SHEAR BLADE SPACER	2	370748	48					WITH LEG
8	FRONT BEND. PLATE	1	1-386017-5	49					505072
9	REAR ANVIL SPACER PLT.			50				CRIMP	SIZE
10	FRONT ANVIL SPACER PLT.	1	1-387158-6	51				WIRE	.110
11	TOOL SPACER	1	470493-6	52				INSUL.	F
12	SPACER	1	1-470493-4	53				SLEEVED	1.000
13	FRONT STRIP GUIDE	1	810144-1	54				INSULATION RANGE	WIRE RANGE
14	REAR STRIP GUIDE	1	810144-2	55					20-16 MAG
15	RAM	1	471167	56				EXPLODED VIEW	
16	TOOL HOLDER	1	376046	57	SCREW, DRIVE	3	21017-6	A-6000	A-6000-1
17	ADJ. CRIMP MOUNT			58	PLATE, IDENTIFICATION	1	452373-1	REMARKS:	
18	ADJ. BLOCK			59				TOP TOOL MTG:	
19	APPLICATOR MOUNT ASSY.	1	570656	60				ITEM 5, 12, 42, 11, 1	
20	BASE PLATE			61				BOTTOM TOOL MTG:	
21	BASE BLOCK			62				ITEM 6, 7, 8, 10, 3	
22	STRIP GUIDE PLATE			63				REAR STRIP GUIDE	
23	ANVIL HOLDER	1	370526	64				ADJUSTMENT REQUIRED	
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ. PLATE	1	374997	WHEN CHANGING FROM	
25	STRIPPER	1	811654-2	66	MISCELLANEOUS			ONE PRODUCT TO THE	
26	STRIPPER MOUNT	2	386231	67				OTHER	
27	RETAINER PLATE	2	372251	68				DENOTES WEARING PARTS	
28	STRIPPER MOUNT BRACKET			69	AIRFEED DELAY ASSY	1	809806-1	RECOMMEND PURCHASE REPLACEMENT	
29	STRIPPER BUSHING			70	LUBRICATOR ASSY	1	465184-2		
30	STOCK DRAG	1	375381	71	TERMINAL LUBRICANT	1	22014-1	THIS APPLICATOR IS TO BE USED ON	
31	STOCK DRAG HANDLE			72	AIR FEED ASSY 2"	1	690021	AMP-O-ELECTRIC 1-471273-2	
32	STOCK DRAG STUD	2	354045-1	REV.	REVISION RECORD	DATE	BY	ECN	
33	STOCK DRAG SPRING	2	1-23847-1	A	ECN R-6296	6-85	JH	EC	
34	STOCK DRAG ADJ. SCREW	2	372997	B	ECN R-6488	10-85	PH	EC	
35	FEED FINGER HOLDER			C	EC-A-262690	8-6-90	PH	EC	
36	FEED FINGER	1	375093	D	0150-6407-95	9/95	PH	EC	
37	FEED FINGER TIP			E	0150-6525-95	11/95	PH	EC	
38	FEED FINGER SPACER			F	ECN 0150-9329-99	5-99	JH	EC	
39	BASE CASTING	1	570238	G	0150-9462-99	7-99	PH	EC	
40	GUARD	1	457664-7						
41									

TO APPLY TERMINAL		505017	
MAG			
WIRE SIZE	CRIMP HEIGHT		
20	.054		
18	.057		
16	.062		
		WITH LEG	
		505072	
CRIMP	SIZE	TYPE	FEED
WIRE	.110	F	
INSUL.			1.000
SLEEVED			
INSULATION RANGE	WIRE RANGE		
	20-16 MAG		
EXPLODED VIEW			
A-6000 A-6000-1			
REMARKS:			
TOP TOOL MTG:			
ITEM 5, 12, 42, 11, 1			
BOTTOM TOOL MTG:			
ITEM 6, 7, 8, 10, 3			
REAR STRIP GUIDE			
ADJUSTMENT REQUIRED			
WHEN CHANGING FROM			
ONE PRODUCT TO THE			
OTHER			
DENOTES WEARING PARTS			
RECOMMEND PURCHASE REPLACEMENT			
THIS APPLICATOR IS TO BE USED ON			
AMP-O-ELECTRIC 1-471273-2			
ALIGN. GA. 679597-1			
SERIAL NO.	DATE SHIPPED	DESIGNED	
		3/29/95	
CUSTOMER NAME AND ADDRESS			
APP'D.			
1/28/95			
APPLICATOR NUMBER	REV.	G 566260-3	
		1 of 1	

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

CASE CODE
00779

CUSTOMER AND ASSEMBLY DRAWING

RESTRICTED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[566260-3](#)