

Technical drawing of a reel-to-reel tape cassette, showing top and side views with dimensions in inches and millimeters.

Top View Dimensions:

- REEL DIA. REF. (Reference diameter)
- FEED DIRECTION (Arrow pointing right)
- .500 [12.7] MIN. DIA. HOLE THRU (Minimum diameter hole through the reel)

Side View Dimensions:

- FEED DIRECTION (Arrow pointing right)
- WIDTH (Overall width of the cassette)
- PITCH (Distance between the two rows of holes)
- .005 [±0.13] (Dimension for the hole diameter)
- .157 (Dimension for the hole diameter)
- .005 [±0.13] (Dimension for the hole diameter)
- .059 [1.5] DIA. HOLE (TYP.) (Typical diameter of the hole)
- .079 [2.0] (Dimension for the hole diameter)
- .177 [4.5] REF. (Reference dimension for the hole diameter)
- .787 [20.0] (Dimension for the hole diameter)
- .016 [0.4] REF. (Reference dimension for the hole diameter)

TAPE AND REEL SPECIFICATIONS:

MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
1.732 [44.0] WIDE; .945 [24.0] PITCH

13.0 [330.2] DIA. 500 PIECES OF
PART NO. 3082 PER REEL.

<h1>KEYSTONE ELECTRONICS CORP.</h1> <p>www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900</p>			
PART NAME <h2>20 mm SM COIN CELL CLIP ON TAPE</h2>			
MATERIAL <h2>AS NOTED</h2>			
FINISH <h2>AS NOTED</h2>		DRN BY <h2>NT</h2>	DATE <h2>3.07.09</h2>
		APP'D <h2>LN</h2>	SCALE <h2>X</h2>
TOLERANCES INCH [MM] DECIMAL ±.015 [± 0.38] ANGULAR $\pm 1^\circ$ UNLESS OTHERWISE SPECIFIED	CODE <h2>C</h2>	DWG NO. <h2>3082TR</h2>	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Keystone Electronics:](#)

[3082TR](#)