







RIB INDICATES
CIRCUIT #1

RECOMMENDED HOLE LAYOUT FOR 1.78 [.070] MAXIMUM THICK PC BOARD.



- 1 MATERIAL: HOUSING-NYLON, UL94V-2
(COLOR-NATURAL, COLOR OF PARTS MAY VARY).
CONTACTS-0.25 [.010] THICK BRASS ALLOY
- 2 CONTACT FINISH: 0.000100 [.0000039] MIN. MATTE TIN
OVER 0.000050 [.0000020] MIN. NICKEL OVER ENTIRE
CONTACT.
- 3 MATES WITH VAL-U-LOK(TM) RECEPTACLE HOUSINGS.

59.4 [2.32]	57.0 [2.24]	55.6 [2.19]	51.6 [2.03]	46.2 [1.82]	24	2-1586585-4
55.2 [2.17]	52.0 [2.08]	51.4 [2.02]	47.4 [1.87]	42.0 [1.65]	22	2-1586585-2
51.0 [2.01]	48.6 [1.91]	47.2 [1.86]	43.2 [1.70]	37.8 [1.49]	20	2-1586585-0
46.8 [1.84]	44.4 [1.75]	43.0 [1.69]	39.0 [1.54]	33.6 [1.32]	18	1-1586585-8
42.6 [1.69]	40.2 [1.58]	38.8 [1.53]	34.8 [1.37]	29.4 [1.58]	16	1-1586585-6
38.4 [1.51]	36.0 [1.42]	34.6 [1.36]	30.6 [1.20]	25.2 [0.99]	14	1-1586585-4
34.2 [1.35]	31.8 [1.25]	30.4 [1.20]	26.4 [1.04]	21.0 [0.83]	12	1-1586585-2
30.0 [1.18]	27.6 [1.09]	26.2 [1.03]	22.2 [0.87]	16.8 [0.66]	10	1-1586585-0
25.8 [1.02]	23.4 [0.92]	22.0 [0.87]	18.0 [0.71]	12.6 [0.50]	8	1586585-8
21.6 [0.85]	19.2 [0.76]	17.8 [0.70]	13.8 [0.54]	8.4 [0.33]	6	1586585-6
17.4 [0.69]	15.0 [0.59]	13.6 [0.54]	9.6 [0.38]	4.2 [0.17]	4	1586585-4
13.2 [0.52]	10.8 [0.43]	9.4 [0.37]	5.4 [0.21]	—	2	1586585-2
(E)	(D)	C	B	(A)	POS	PART NUMBER

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.		DNN 12-NOV-2004 S. HOOVER CHK 12-NOV-2004 D. COLEY		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0.13 [0.005] 0.30 [0.012]		NAME VERTICAL HEADER ASSEMBLY - BLINDMATE WITH DRAIN HOLES, VAL-U-LOK(TM)	
		APVD 12-NOV-2004 D. COLEY PRODUCT SPEC APPLICATION SPEC		SIZE A1	
MATERIAL FINISH		WEIGHT		CAGE CODE 00779	
		CUSTOMER DRAWING		DRAWING NO 1586585	
				SCALE 5:1	
				SHEET 1 of 1	
				REV A	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1586585-2](#)