



The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

Applications


- Various commercial applications
- Electric guitars
- Sound processing equipment
- Guitar and sound system amplifiers
- Appliances

PDB24 Series - 24 mm Rotary Potentiometer


BOURNS®

Product Dimensions


F Type



P Type



K Type



DIMENSIONS: $\frac{\text{MM}}{(\text{INCHES})}$

How To Order

PDB24 1 - E 4 25 K - 103 A2

Model

No. of Sections

- 1 = Single Section/Standard Rotational Life
- 2 = Single Section/High Rotational Life

Terminal Configuration (Pin Layout)
(see individual drawings)

- E = Solder Lugs Rear Facing
- S = Solder Lugs Down Facing
- D = PC Pins Front Facing

Detent Option

- 2 = Center Detent
- 4 = No Detents

Standard Shaft Length

- 20 = 20 mm
- 25 = 25 mm
- 30 = 30 mm

Shaft Style

- K = Metal Knurled Type Shaft
- 18 Toothed Serration Type
- F = Metal Flatted Shaft
- P = Metal Plain Shaft

Resistance Code (See Table)

Resistance Taper (See Taper Chart)




Taper Series followed by Curve Number

Other styles available.

Standard Resistance Table

Resistance (Ohms)	Resistance Code
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105

Tapers



REV. 03/17

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bourns:

[PDB242-E420K-504A2](#) [PDB242-E420K-254A2](#) [PDB241-E420P-254A2](#) [PDB241-E420P-103B0](#) [PDB241-E420K-504B0](#) [PDB241-E420P-504B0](#) [PDB241-E420K-254B0](#) [PDB241-S420K-504A2](#) [PDB241-E420P-504A2](#) [PDB241-S420P-504A2](#) [PDB241-E420K-254A2](#) [PDB241-S420P-254A2](#) [PDB241-E420K-103B0](#) [PDB241-S420P-103B0](#) [PDB241-E420P-254B0](#) [PDB241-S420K-103B0](#) [PDB241-S420K-254A2](#) [PDB241-E420K-504A2](#) [PDB241-E420K-104B0](#) [PDB241-E420K-105A2](#) [PDB241-E425K-504A2](#) [PDB241-S420K-103B2](#) [PDB242-E220F-103B0](#) [PDB242-E420F-103B1](#) [PDB241-E430P-253B0](#) [PDB242-E220K-202B5](#) [PDB242-E420K-502A2](#) [PDB242-E430P-504A2](#) [PDB241-E430P-502B0](#) [PDB242-E420P-254A2](#) [PDB241-E420P-105A1](#) [PDB242-E420P-105A2](#) [PDB241-E430P-504A3](#) [PDB242-D220K-503A1](#) [PDB241-E420F-102B0](#) [PDB241-E420F-103B0](#) [PDB241-E420P-504A1](#) [PDB241-E420P-203B0](#) [PDB242-D425P-104A1](#) [PDB242-S425K-104B2](#) [PDB241-S220K-203B2](#) [PDB242-E430P-105A2](#) [PDB241-E420P-105A2](#) [PDB241-S220F-502B0](#) [PDB242-E420P-105A1](#) [PDB242-D425P-103A1](#) [PDB241-E420P-503A2](#) [PDB242-E420P-503A2](#)