

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	N	REVISED PER ECO-12-014020	01AUG2012	RW SY

Technical drawing of a contact strip showing dimensions: .725 REF, .520 REF, .050 REF, and A SPACES AT .050 = B.

# OBSOLETE

FFC RCPT CONTACT  
 .058 REF TYP

① NICKEL .000050 MIN THK UNDERPLATE ON ENTIRE CONTACT, WITH GOLD .000030 MIN THK ON MATING AREA, AND BRIGHT TIN/LEAD .000100 MIN THK ON CRIMP AREA,  
 -OR-  
 NICKEL .000050 MIN THK UNDERPLATE ON ENTIRE CONTACT, GOLD FLASH OVER PALLADIUM-NICKEL, .000030 MIN TOTAL THK ON MATING AREA AND BRIGHT TIN/LEAD .000100 MIN THK ON CRIMP AREA.

② LENGTH AFTER BEING CUT-OFF FROM CARRIER STRIP.

3. TO BE TERMINATED TO FLEXIBLE FLAT CONDUCTOR CABLE IN APPLICATOR 818973-1.

4. MIN MATING POST LENGTH .125.

⑤ NICKEL .000050 MIN THK UNDERPLATE ON ENTIRE CONTACT, WITH GOLD .000030 MIN THK ON MATING AREA, AND GOLD FLASH ON CRIMP AREA,  
 -OR-  
 NICKEL .000050 MIN THK UNDERPLATE ON ENTIRE CONTACT, GOLD FLASH OVER PALLADIUM-NICKEL, .000030 MIN TOTAL THK ON MATING AREA AND GOLD FLASH ON CRIMP AREA.

OBSOLETE	1-487547-1	⑤	1.450	29	30	4-487558-8
OBSOLETE	487547-1	①	2.450	49	50	4-487558-7
OBSOLETE	487547-1	①	2.200	44	45	4-487558-2
OBSOLETE	487547-1	①	1.950	39	40	3-487558-7
OBSOLETE	487547-1	①	1.750	35	36	3-487558-3
OBSOLETE	487547-1	①	1.650	33	34	3-487558-1
OBSOLETE	487547-1	①	1.450	29	30	2-487558-7
OBSOLETE	487547-1	①	1.200	24	25	2-487558-2
OBSOLETE	487547-1	①	1.050	21	22	1-487558-9
OBSOLETE	487547-1	①	.950	19	20	1-487558-7
OBSOLETE	487547-1	①	.800	16	17	1-487558-4
OBSOLETE	487547-1	①	.700	14	15	1-487558-2
OBSOLETE	487547-1	①	.600	12	13	1-487558-0
OBSOLETE	487547-1	①	.550	11	12	487558-9
OBSOLETE	487547-1	①	.500	10	11	487558-8
OBSOLETE	487547-1	①	.450	9	10	487558-7
OBSOLETE	487547-1	①	.350	7	8	487558-5
SUPSD BY	487547-1	①	.300	6	7	487558-4
OBSOLETE	487547-1	①	.250	5	6	487558-3
OBSOLETE	487547-1	①	.200	4	5	487558-2
OBSOLETE	487547-1	①	.150	3	4	487558-1

RCPT CONTACT PART NO (REF)	FINISH	B	A	NO OF POSN	PART NO
THIS DRAWING IS A CONTROLLED DOCUMENT.					
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN 10-28-85 D.DOLLYHIGH	
0 PLC ± -		1 PLC ± -		CHK 10-28-85 D.R.WORTHINGTON	
2 PLC ± -		3 PLC ± .005		APVD -	
4 PLC ± -		ANGLES ± -		NAME	
MATERIAL PHOSPHOR BRONZE		FINISH SEE TABLE		PRODUCT SPEC 108-16022	
				APPLICATION SPEC 114-16008	
				WEIGHT -	
				SIZE A2 CAGE CODE 00779 C=487558	
				DRAWING NO	
				RESTRICTED TO	
				SCALE 4:1 SHEET 1 OF 1 REV N	
				CUSTOMER DRAWING	

1471-9 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[4-487558-8](#)