



|                                    |                  |                      |                  |
|------------------------------------|------------------|----------------------|------------------|
| Current - Maximum per Contact      | 0.75A            | Backplane Signal     | <u>622018662</u> |
| Data Rate                          | 25.0 Gbps        | Module Assembly      |                  |
| Impedance                          | 100Ω             | Press-In Tool for 6- |                  |
| Shield Type                        | N/A              | Pair by 10-Column    |                  |
| Shielded                           | No               | Assemblies           |                  |
| Voltage - Maximum                  | 30V AC (RMS)/DC  |                      |                  |
| <b>Solder Process Data</b>         |                  |                      |                  |
| Lead-freeProcess Capability        | N/A              |                      |                  |
| <b>Material Info</b>               |                  |                      |                  |
| <b>Reference - Drawing Numbers</b> |                  |                      |                  |
| Application Specification          | AS-76060-990-001 |                      |                  |
| Packaging Specification            | PK-70873-7703    |                      |                  |
| Product Specification              | PS-76060-999-001 |                      |                  |
| Sales Drawing                      | SD-76145-001-001 |                      |                  |
| Symbol/Footprint Data              | SYM-76145-1105   |                      |                  |

This document was generated on 09/12/2019

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[76145-1105](#)