PART NUMBER	SSP-1156B157U12	REV.	D
DATE	E.C.N. NUMBER AND REVISION COMMENTS		
2.26.03	E.C.N. #10956.		Α
8.19.03	E.C.N. #11025.		В
11.5.03	E.C.N. #11050.		С
07.22.11	E.C.N. #11741.		D

TYP

470

12.0

13500

30

ELECTRO-OPTICAL CHARACTERISTICS TA = 25°C

5.0

BLUE WATER CLEAR LENS

PARAMETER

PEAK WAVELENGTH

FORWARD VOLTAGE


REVERSE VOLTAGE


AXIAL INTENSITY

VIEWING ANGLE

EMITTED COLOR:

EPOXY LENS FINISH:





LIMITS OF SAFE OPERATION AT 25°C	PER MODULE	
PARAMETER	MAX	UNITS
PEAK FORWARD VOLTAGE	14	mA
STEADY CURRENT	110	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-40 TO +85	•c
STORAGE TEMP.	-40 TO +85	.c

Vf =12V

UNITS

nm

mcd

2x theta


MAX

14.0

TEST COND

I_r=100uA

 $V_f = 12V$



CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+DECIMAL}_{-0.00}$ PRECISION MAX.= $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.00}$ PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD SIZE=±0.05 (±0.030). MIN= $^{+0.00}_{-0.00}$ MAX.= $^{+0.0$ INCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

1156 LED REPLACEMENT LAMP, BLUE.

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

N	DIVC	DIVITULL	ED DOCUMENT		
	DATE:	05.06.02	DRAWN BY:	ВС	
	PAGE:	1 OF 1	CHKD BY:	KF	
	SCALE:	NTS	APRVD BY:	SS	
	UNIT: mm [INCH]		P6		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSP-1156B157U12