




| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 46.6              |
| B   | 25.4              |
| C   | 1 7/16-18UNEF-2A  |
| D   | 9.5               |
| E   | 59                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICKTKÖRPER / GROMMET                |
| 4   | ENDRING / ENDRING                    |
| 5   | KONTAKTSTIFT/ CONTACT PIN            |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 14  | F-ENDGEHÄUSE / F-ENDBELL             |

|                                                                                                    |
|----------------------------------------------------------------------------------------------------|
| Note: Due to an automatic nomenclature system, numbers generated may not be sequential.            |
| Specification and Dimensions subject to change<br>Drawings illustrate normal insulator positioning |

|                                                              |
|--------------------------------------------------------------|
| Material Specification:                                      |
| Shell Material: Aluminium alloy                              |
| Shell Plating: Olive drab chromate over cadmium (conductive) |
| Insulator Material: CR-Elastomere                            |
| Contact Material: Copper alloy                               |
| Contact Plating: Hard silver                                 |

|                                                                                                                                                                                     |                                                                           |                                                                                                                                                                                            |                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| all dimensions are in mm<br>Dimensions without tolerance indications are general tolerances in acc. with DIN7168m                                                                   |                                                                           | drawing for<br>CUSTOMER                                                                                                                                                                    |                            |
| <br><b>ITT</b><br><i>Engineered for life</i><br>ITT CANNON GmbH<br>D - 71384 Weinstadt/Germany | description CA3106F24-5P-B-F80                                            |                                                                                                                                                                                            |                            |
|                                                                                                                                                                                     | Plug, straight<br>Endbell for flex tube<br>AWG Crimp / Pin / Layout: 24-5 |                                                                                                                                                                                            |                            |
| © All rights reserved. Reproduction or issue to third in any form<br>whatever is only permitted with written authorization of ITT Cannon                                            |                                                                           | <br><br>page 1/1 | revision<br>1862 1. Jul 20 |