

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

H

-

F4

8-188431-6 ACTIVATED

20AUG2014

NV

JK

NOTES:

- 1 PACKAGING ACCORDING EIA-481/ DIN IEC 286
- 2 QUANTITY PER REEL 1200 PCS. REEL DIA. 380 MM
- 3 PN 9-188431-0 (20 POSITIONS) AS DRAWN.
- 4 3.0 - 5.0 μ m TIN OVER 0.5 μ m NICKEL PLATING.
- 5 PICK & PLACE AREA.

PACKAGING/REELING DIRECTION

USER DIRECTION OF FEED

see detail A

DETAIL A
SCALE 1:1

SECTION A-A

RECOMMENDED PC- BOARD PAD LAYOUT

SCALE 3:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC

 $\pm$

-

1 PLC

 $\pm$

0.2

2 PLC

 $\pm$

-

3 PLC

 $\pm$

-

4 PLC

 $\pm$

-

ANGLES

 $\pm$

-

FINISH

 $\pm$

-

MATERIAL

SEE TABLE

SEE TABLE

DWN 25/09/00

M.Gosselink

CHK

M.Gosselink

APVD

-

PRODUCT SPEC

108-19052

APPLICATION SPEC

114-13318

WEIGHT

-

CUSTOMER DRAWING

TE

TE Connectivity

NAME
MICRO MATCH, FEMALE BOTTOM ENTRY
SMD INBOARD CONNECTOR

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

C-

188431

SCALE 4:1

SHEET 1 OF 1

REV F4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[7-188431-6](#)