


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: **0457730003**
Status: **Active**
Overview: Micro-Fit Connector System
Description: Micro-Fit 3.0 Crimp Terminal, Female, with Lubricant, with Gold (Au) Plated Phosphor Bronze Contact, 20-24 AWG, Reel

Documents:

Drawing (PDF)	Test Summary TS-43045-001-001 (PDF)
Product Specification PS-43045 (PDF)	Test Summary TS-43045-002-001 (PDF)
Product Specification PS-43650 (PDF)	RoHS Certificate of Compliance (PDF)
Packaging Specification PK-45773-001-001 (PDF)	



General

Product Family	Crimp Terminals
Series	45773
Application	Power
Crimp Quality Equipment	Yes
Overview	<u>Micro-Fit Connector System</u>
Product Name	Micro-Fit 3.0
UPC	822348293964

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	0.067/g
Packaging Type	Reel
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.85mm max.
Wire Size AWG	20, 22, 24
Wire Size mm ²	N/A

Electrical

Current - Maximum per Contact	8.5A
-------------------------------	------

Solder Process Data

Lead-freeProcess Capability	N/A
-----------------------------	-----

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-45773-001-001
Product Specification	PS-43045, PS-43650
Sales Drawing	SD-45773-001
Test Summary	TS-43045-001-001, TS-43045-002-001

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - ED/71/2019 (16 July 2019)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

45773 Series

Mates With

43031 Micro-Fit 3.0 Male Crimp Terminals

Use With

43025 , 43645 Micro-Fit 3.0 Receptacle Housings, 44133 Micro-Fit BMI Panel Mount Receptacle Housings

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Extraction Tool	11030043
Insertion Tool for Micro-Fit 3.0 and CRC Male and Female Crimp	638120800

Terminals, 20-30
AWG
Hand Crimp Tool [638190000](#)
FineAdjust Applicator [639004500](#)
for Insulation OD
1.30-1.85mm, 20-24
AWG Wire
FineAdjust Applicator [639018800](#)
for Insulation OD
1.10-1.30mm - 20-24
AWG
FineAdjust Applicator [639018900](#)
for Insulation OD
0.91-1.09mm - 20-24
AWG
T2 Terminator [639104500](#)
for Insulation OD
1.30-1.85mm, 20-24
AWG
T2 Terminator [639118800](#)
for insulation OD
1.10-1.30mm - 20-24
AWG
T2 Terminator [639118900](#)
for insulation OD
0.91-1.09mm - 20-24
AWG

This document was generated on 09/19/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[45773-0003](#)