



**Product: 38308** ☑

UL Type PV Wire, #8 Str TC, XLPO Ins, PVC Jkt, 2000V PV 90C Dry/Wet

# **Product Description**

UL Type PV Wire, 8AWG (133(7x19)x29) Tinned Copper, XLPO Insulation, PVC Outer Jacket, 2000V PV 90C Dry/Wet USE-2 RHW-2 SUN RES

# **Technical Specifications**

# **Product Overview**

Suitable Applications: Interconnection wiring of grounded and ungrounded photovoltaic power systems as described in Section 690.31(A) of the 2008 NEC.

# **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Conductors
8	133x29	TC - Tinned Copper	1
Condu	ctor Count:		1

#### Insulation

Material	Nominal Wall Thickness
XLP, XLPO, XLPE (Thermoset)	0.073 in
XLP, XLPO, XLPE (Thermoset)	

### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.384 in	0.033 in

# **Electrical Characteristics**

## Conductor DCR

Nominal Conductor DCR 0.61 Ohm/1000ft

# Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30 ambient	80.0 A

#### Voltage

Non-UL Voltage Rating	<b>UL Description</b>	UL Voltage Rating
600 V	PV, RHW-2	2000 V
	USE-2	600 V RMS

# **Temperature Range**

UL Temp Rating:	90°C
Operating Temp Range:	-40°C To +90°C

# **Mechanical Characteristics**

Bulk Cable Weight:	96 lbs/1000ft
Max Recommended Pulling Tension:	213 lbs

Min Bend Radius/Minor Axis:	3.875 in

#### **Standards**

UL AWM Style:	PV, USE-2, RHW-2
Military Specification:	N/A

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2009-09-01
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Sunlight Resistance:	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	2000 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N): No
------------------

## **Part Number**

#### Variants

Item #	Color	Putup Type	Length	UPC
38308 0105000	Black	Reel	5,000 ft	612825147701
Footnote:			C -	CRATE REEL PU

## History

Update and Revision:	Revision Number: 0.269 Revision Date: 04-28-2020

## © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 38308 0101000 38308 0105000