2/05 DRL DRL   EV DATE BY CHK			ADDED UL, CSA AND PART NO. TO STAMP DESCRIPTION			SCALE N/A DRAWING NO / CAD FILE LCA1_0-38F-CUST
					12473	LCA1/0-38F-X Copper Lug - One-Hole, Standard Barrel, 90° Angle Tongue
	C	ERTIFIE	B USTED D LISTED Wire Connector		39±.01 — 52±.01 — — 1.58	
Alternate Industry Die Index No. ( ) on Barrel			(12)			.94±.04
Panduit Die Index No. on Barrel		ex No.	P42		90°±5°	1.54 REF PANDUIT
Panduit Color Code on Barrel		ode	PINK	.12±.01 —		
C.S.A Certified Wire Connector			Yes			
UL Temperature Rating			90°C			
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		3±.04 —	.41±.02 DIA
Stud Size			3/8 in.	.36±.04 —		41±.02 DIA
Wire Strip Length		ı	1.0 in.			
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	.76±.04	1/0 STR C	
Wire Size			1/0 AWG		CU	Wire inspection window
Plating			Electro-Tin	-		
Material			High Conductivity Seamless Copper Tube	]		

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit: LCA1/0-38F-X