OW-PROFILE 025" SQ POST HEADER

(2.54 mm) .100" PITCH • TLW/MTLW SERIES

MTLW



BSW, CES, SLW, HLE

FEATURES

These headers provide the ultimate low-profile (0.64 mm) .025" square post board stacking system. The high quality Phosphor Bronze terminals are available with a standard short post height (TLW Series) for mating with low-profile sockets, or the post height can be Modified (MTLW Series) to accommodate IDC assemblies and other applications.

SPECIFICATIONS

Insulator Material: Black Liquid Crystal Polymer
Terminal Material: Phosphor Bronze

Phosphor Bronze
Plating:
Au or Sn over
50 µ" (1.27 µm) Ni
Current Rating (TLW/SLW): 5.2 A per pin (2 pins powered) **Operating Temp Range:** -55 °C to +105 °C with Tin -55 °C to +125 °C with Gold

PROCESSING

Lead-Free Solderable:

ALSO AVAILABLE

Other platings Notch option


Some lengths, styles and options are non-standard, non-returnable. MTLW Series is non-standard, nonreturnable.




PER ROW


01 thru 40 = Single Row

01 thru 36 = Double Row









PLATING OPTION

Specify LEAD **STYLE** from chart

STYLE

-G $= 10 \mu''$ $(0.25 \ \mu m)$ Gold on post, Gold flash on tail

Gold flash

on post,

Matte Tin

on tail

-T = Matte Tin

ROW **OPTION**

- S = Single Row

– D = Double Row

OTHER OPTION

-RA = Right-angle (-01 Lead Style only)

-"XX"= Polarized Position
Specify position for
omitted pin.

| LEAD STYLE | A | В |
|---------------|----------------|----------------|
| -01 | N/A | (5.84) .230 |
| -05 | (4.32) .170 | (2.67) .105 |
| -06 | (3.43) .135 | |

NO. PINS PER ROW

(2.54) .100 x No. of Positions

◊

01 thru 40 = Single Row

> 01 thru 36 = Double Row

(5.03)

LEAD STYLE

Specify LEAD **STYLE** from

PLATING


chart

= Gold flash on post, Matte Tin on tail

= 10 µ" (0.25 µm) Gold on post, Matte Tin on tail

= 10 μ" (0.25 μm) Gold on post, Gold flash on tail

> -T = Matte Tin



ROW OPTION

- S = Single Row

- D = Double Row

POST

HEIGHT

| LEAD STYLE | OAL |
|---------------|--------------|
| -05 | (8.51) .335 |
| -06 | (7.62) .300 |
| -07 | (10.92) .430 |
| -08 | (13.46) .530 |
| -09 | (18.54) .730 |
| -10 | (21.08) .830 |
| -22 | (16.00) .630 |
| -23 | (11.30) .445 |
| -24 | (12.19) .480 |

(2.48)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

TLW-106-05-T-S