


# Product data sheet

## Characteristics

# XZCP0466L5

pre-wired connectors XZ - elbowed female - Ø 8 mm - 3 pins - cable PUR 5m

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	General purpose
Electrical connection	Elbowed female connector Ø 8 mm, 3 pins
Status LED	2 NPN LEDs
Cable length	16.4 ft (5 m)

### Complementary

Cable connector fixing	Clip-on
Cable outer diameter	0.2 in (5.2 mm)
Cable composition	3 x 0.34 mm <sup>2</sup>
Wire insulation material	PUR
[Ue] rated operational voltage	10...30 V DC
[In] rated current	4 A
Contact resistance	<= 5000 µOhm
Insulating resistance	>= 1 GΩ
Product weight	0.24 lb(US) (0.11 kg)

### Environment

IP degree of protection	IP65
Ambient air temperature for operation	23...176 °F (-5...80 °C) (flexing) -40...176 °F (-40...80 °C) (static)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)

### Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110763058
Nbr. of units in pkg.	1
Package weight(Lbs)	0.27
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	DE

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0726 - <a href="#">Schneider Electric declaration of conformity</a>

### Contractual warranty

Period	18 months
--------	-----------

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XZCP0466L5](#)