

Specification Sheet

Part Number: FCST



Connector, Fiber Optic ST Multimode 900µm, 2mm, 3mm Simplex–Epoxy & Polish, 1/Pkg

Article Number

855-14203

Type

FCST

Features & Benefits

- Use with epoxy or anaerobic adhesives for different applications or user preference.
- Pre-radiused zirconia ceramic ferrules provide precision installation.
- Meet ANSI/TIA/EIA 568-C standards.
- Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.

Quantity Per

bag

Product Description

Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation. Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing

Short Description	Connector, Fiber Optic ST Multimode 900µm, 2mm, 3mm Simplex–Epoxy & Polish, 1/Pkg
Global Part Name	FCST
Technical Description	ST Multimode Fiber Connector
Port Count	1
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Customs Number	8536700000