


Male Style H 11




Series 8450 – single row (1 x 11)




Contact Design and Termination Length	Number of Contacts	Loading Description	Part Number
			Performance classes according to DIN 41612
Faston (6.3 x 0.8)	11	fully loaded	10 8450 011 001 169
		fully loaded + ground in first & last position	10 8450 011 101 169
		fully loaded + keying*	12 8450 011 001 169
		fully loaded + keying + ground in first & last position	12 8450 011 101 169
3.0mm (1.2 x 0.8mm) Right Angled PC solder	11	fully loaded	10 8450 011 002 169
		fully loaded + ground in first & last position	10 8450 011 102 169
		fully loaded + keying*	12 8450 011 002 169
		fully loaded + keying + ground in first & last position	12 8450 011 102 169

NB: Connectors with Keying also require 10 pieces per connector pair of p/n 80 8456 8814 00 000
Additional Plating & Loading Variations: Please contact your local AVX sales office or distributor.

LOADING DESCRIPTION




11 contacts, fully loaded



11 contacts, fully loaded with ground z1 & z32

△ denotes ground pin

DIMENSIONS



Female Style H 11




Series 8450 – single row (1 x 11)




Contact Design and Termination Length	Number of Contacts	Loading Description	Part Number
			Performance classes according to DIN 41612
Faston (6.3 x 0.8)	11	fully loaded	20 8450 011 001 169
	11	fully loaded with keying*	22 8450 011 001 169

NB: Connectors with Keying also require 10 pieces per connector pair of p/n 80 8456 8814 00 000
 Additional Plating & Loading Variations: Please contact your local AVX sales office or distributor.

LOADING DESCRIPTION



DIMENSIONS



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[AVX:](#)

[208450011001169](#) [108450011001169](#) [108450011002169](#) [108450011101169](#) [108450011102169](#)
[128450011001169](#) [228450011001169](#)