

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1		2		3		4		5		6		7		8					
A		B		C		D		E		F									
COUNT		DESCRIPTION OF REVISIONS		BY		CH#0		DATE		COUNT		DESCRIPTION OF REVISIONS		BY		CH#0		DATE	
△								..		△								..	
△								..		△								..	
△								..		△								..	

HRS NO	PART NO	A	B
CL541-0200-6	DF1B- 2S-2.5R	5.0	2.5
CL541-0201-9	DF1B- 3S-2.5R	7.5	5.0
CL541-0202-1	DF1B- 4S-2.5R	10.0	7.5
CL541-0203-4	DF1B- 5S-2.5R	12.5	10.0
CL541-0204-7	DF1B- 6S-2.5R	15.0	12.5
CL541-0205-0	DF1B- 7S-2.5R	17.5	15.0
CL541-0206-2	DF1B- 8S-2.5R	20.0	17.5
CL541-0207-5	DF1B- 9S-2.5R	22.5	20.0
CL541-0208-8	DF1B-10S-2.5R	25.0	22.5
CL541-0209-0	DF1B-11S-2.5R	27.5	25.0
CL541-0210-0	DF1B-12S-2.5R	30.0	27.5
CL541-0211-2	DF1B-13S-2.5R	32.5	30.0
CL541-0212-5	DF1B-14S-2.5R	35.0	32.5
CL541-0213-8	DF1B-15S-2.5R	37.5	35.0
CL541-0214-0	DF1B-16S-2.5R	40.0	37.5
CL541-0215-3	DF1B-18S-2.5R	45.0	42.5
CL541-0216-6	DF1B-20S-2.5R	50.0	47.5

NOTE 1 2 positions socket have one polarizing slot at senter.
3 TO 6 positions have 2 polarizing slots at both ends.
Other positions have 3 polarizing slots as per drawing.

TO

CODE NO. (OLD) CL		DRAWN Y. Inoue		DESIGNED Y. Inoue		CHECKED T. Miyagaki		APPROVED K. Katayama		RELEASED	
SCALE 2 : 1		DRAWING NO. EDC3-160017		PART NO. DF1B-*S-2.5R		MATERIAL POLYAMIDE		FINISH, REMARKS NATURAL (WHITE), UL94V-0			
UNITS mm		HIROSE ELECTRIC CO., LTD		CODE NO. CL541							