


REV. 0  
DCO 144068

COIL: @ 25°C	
RESISTANCE	3200 OHMS ±10%
NOMINAL VOLTAGE	26.5 VDC
MUST OPERATE	15.2 VDC
MUST RELEASE	10.8 VDC MAX, 1.7 VDC MIN.

ENVIRONMENT:	
VIBRATION	10 Hz TO 3000 Hz @ 30 g's
SHOCK	75 g's 6 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C
NOTES: OPERATE TIME 4.0 MS MAX	
RELEASE TIME 7.5 MS MAX	
CONTACT BOUNCE TIME 1.5 MS MAX.	

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1 AMP  
28 VDC RESISTIVE 100,000 OPERATIONS MIN

DR. ASB 29JUN2005

CK. JERRY C. 6/29/05

**CII Technologies™**  
advanced control electronic solutions

CUST. QPL  
CUST. NO. M39016/43-062L REV.

"JMGSDD" RELAY

JMGSCDDG-26LW

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGSCDDG-26LW](#)