

Surface Mount Type

Series: **ZC** Type: **V**

High temperature lead-free reflow

UP GRADE



Features

- Endurance: 4000 h at 125 °C (High temperature / Long life)
- Low ESR and high ripple current (85 % over, Lower ESR than current V-TP)
- High-withstand voltage (to 80 V.DC), Low LC (0.01 CV or 3 μA)
- Equivalent to conductive polymer type aluminum electrolytic capacitor
(There are little characteristics change by temperature and frequency)
- Vibration-proof product is available upon request. New lineup of φ6.3 product. (φ6.3, φ8, φ10)
- AEC-Q200 compliant
- RoHS compliant

Specifications

Size code	C	D	D8	F	G
Category temp. range	-55 °C to +125 °C				
Rated voltage range	25 V.DC to 50 V.DC		25 V.DC to 63 V.DC		25 V.DC to 80 V.DC
Nominal cap.range	10 μF to 33 μF	10 μF to 56 μF	22 μF to 100 μF	22 μF to 220 μF	33 μF to 330 μF
Capacitance tolerance	±20 % (120 Hz / +20 °C)				
DC leakage current	I ≤ 0.01 CV or 3 (μA) After 2 minutes (whichever is greater)				
Dissipation factor (tan δ)	Please see the attached characteristics list				
Endurance 1	+125 °C ± 2 °C, 4000 h, apply the rated ripple current without exceeding the rated voltage.				
	Capacitance change	Within ±30% of the initial value			
	Dissipation factor (tan δ)	≤ 200 % of the initial limit			
	ESR	≤ 200 % of the initial limit			
Endurance 2	+125 °C ± 2 °C, 3000 h, apply the rated ripple current without exceeding the rated voltage.				
	Capacitance change	Within ±30% of the initial value			
	Dissipation factor (tan δ)	≤ 200 % of the initial limit			
	ESR	≤ 300 % of the initial limit			
Shelf life	After storage for 1000 hours at +125 °C ± 2 °C with no voltage applied and then being stabilized at +20 °C, capacitors shall meet the limits specified in endurance. (With voltage treatment)				
	DC leakage current	Within the initial limit			
Damp heat (Load)	+85 °C ± 2 °C, 85 % to 90 %, 2000 h, rated voltage applied				
	Capacitance change	Within ±30% of the initial value			
	Dissipation factor (tan δ)	≤ 200 % of the initial limit			
	ESR	≤ 200 % of the initial limit			
Resistance to soldering heat	After reflow soldering and then being stabilized at +20 °C, capacitors shall meet the following limits.				
	Capacitance change	Within ±10% of the initial value			
	Dissipation factor (tan δ)	Within the initial limit			
DC leakage current	Within the initial limit				

Marking

Example : 25 V.DC 33 μF
Marking color : BLACK

Rated voltage mark

E	25	J	63
V	35	K	80
H	50		

Unit : V.DC

Dimensions (not to scale)

() Reference size

Unit : mm

Size code	φD	L	A,B	H	I	W	P	K
C	5.0	5.8±0.3	5.3	6.5 max.	2.2	0.65±0.1	1.5	0.35 ^{+0.15} _{-0.20}
D	6.3	5.8±0.3	6.6	7.8 max.	2.6	0.65±0.1	1.8	0.35 ^{+0.15} _{-0.20}
D8	6.3	7.7±0.3	6.6	7.8 max.	2.6	0.65±0.1	1.8	0.35 ^{+0.15} _{-0.20}
F	8.0	10.2±0.3	8.3	10.0 max.	3.4	0.90±0.2	3.1	0.70±0.2
G	10.0	10.2±0.3	10.3	12.0 max.	3.5	0.90±0.2	4.6	0.70±0.2

*The dimensions of the vibration-proof products, please refer to the page of the mounting specification.

Characteristics list

Endurance 1 : 125 °C 4000 h

Endurance 2 : 125 °C 3000 h

Rated voltage (V.DC)	Capacitance (±20 %) (μF)	Case size (mm)		Size code	Specification				Part number		Min. packaging qty
		φD	L		Ripple current *1 (mA r.m.s.)	ESR*2 (mΩ)	tan δ *3	Standard Product	Vibration-proof product	Taping (pcs)	
25	33	5.0	5.8	C	550	-	80	0.14	EEHZA1E330R	-	1000
	56	6.3	5.8	D	900	-	50	0.14	EEHZA1E560P	-	1000
	100	6.3	7.7	D8	1400	-	30	0.14	EEHZA1E101XP	EEHZA1E101XV	900
	220	8.0	10.2	F	1600	1900	27	0.14	EEHZA1E221P	EEHZA1E221V	500
	330	10.0	10.2	G	2000	2900	20	0.14	EEHZA1E331P	EEHZA1E331V	500
35	22	5.0	5.8	C	550	-	100	0.12	EEHZA1V220R	-	1000
	47	6.3	5.8	D	900	-	60	0.12	EEHZA1V470P	EEHZA1V470V	1000
	68	6.3	7.7	D8	1400	-	35	0.12	EEHZA1V680XP	EEHZA1V680XV	900
	150	8.0	10.2	F	1600	1900	27	0.12	EEHZA1V151P	EEHZA1V151V	500
	270	10.0	10.2	G	2000	2800	20	0.12	EEHZA1V271P	EEHZA1V271V	500
50	10	5.0	5.8	C	500	-	120	0.10	EEHZA1H100R	-	1000
	22	6.3	5.8	D	750	-	80	0.10	EEHZA1H220P	EEHZA1H220V	1000
	33	6.3	7.7	D8	1100	-	40	0.10	EEHZA1H330XP	EEHZA1H330XV	900
	68	8.0	10.2	F	1250	-	30	0.10	EEHZA1H680P	EEHZA1H680V	500
	100	10.0	10.2	G	1600	-	28	0.10	EEHZA1H101P	EEHZA1H101V	500
	120	10.0	10.2	G	1600	-	28	0.10	EEHZA1H121P	EEHZA1H121V	500
63 NEW	10	6.3	5.8	D	700	-	120	0.08	EEHZA1J100P	EEHZA1J100V	1000
	22	6.3	7.7	D8	900	-	80	0.08	EEHZA1J220XP	EEHZA1J220XV	900
	33	8.0	10.2	F	1100	-	40	0.08	EEHZA1J330P	EEHZA1J330V	500
	47	8.0	10.2	F	1100	-	40	0.08	EEHZA1J470P	EEHZA1J470V	500
	56	10.0	10.2	G	1400	-	30	0.08	EEHZA1J560P	EEHZA1J560V	500
	68	10.0	10.2	G	1400	-	30	0.08	EEHZA1J680P	EEHZA1J680V	500
	82	10.0	10.2	G	1400	-	30	0.08	EEHZA1J820P	EEHZA1J820V	500
	22	8.0	10.2	F	1050	-	45	0.08	EEHZA1K220P	EEHZA1K220V	500
80	33	10.0	10.2	G	1360	-	36	0.08	EEHZA1K330P	EEHZA1K330V	500
	47	10.0	10.2	G	1360	-	36	0.08	EEHZA1K470P	EEHZA1K470V	500

*1: Ripple current (100 kHz / +125 °C)

*2: ESR (100 kHz / +20 °C)

*3: tan δ (120 Hz / +20 °C)

• Please refer to the page of "Reflow profile" and "The taping dimensions".

• The dimensions of the vibration-proof products, please refer to the page of the mounting specification.

Frequency correction factor for ripple current

Rated capacitance (C)	Frequency (f)	100Hz ≤ f < 200Hz	200Hz ≤ f < 300Hz	300Hz ≤ f < 500Hz	500Hz ≤ f < 1kHz
C < 47μF	Correction factor	0.10	0.10	0.15	0.20
47μF ≤ C < 150μF		0.15	0.20	0.25	0.30
150μF ≤ C		0.15	0.25	0.25	0.30
Rated capacitance (C)	Frequency (f)	1kHz ≤ f < 2kHz	2kHz ≤ f < 3kHz	3kHz ≤ f < 5kHz	5kHz ≤ f < 10kHz
C < 47μF	Correction factor	0.30	0.40	0.45	0.50
47μF ≤ C < 150μF		0.40	0.45	0.55	0.60
150μF ≤ C		0.45	0.50	0.60	0.65
Rated capacitance (C)	Frequency (f)	10kHz ≤ f < 15kHz	15kHz ≤ f < 20kHz	20kHz ≤ f < 30kHz	30kHz ≤ f < 40kHz
C < 47μF	Correction factor	0.60	0.65	0.70	0.75
47μF ≤ C < 150μF		0.70	0.75	0.80	0.80
150μF ≤ C		0.75	0.80	0.85	0.85
Rated capacitance (C)	Frequency (f)	40kHz ≤ f < 50kHz	50kHz ≤ f < 100kHz	100kHz ≤ f < 500kHz	500kHz ≤ f
C < 47μF	Correction factor	0.80	0.85	1.00	1.05
47μF ≤ C < 150μF		0.85	0.90	1.00	1.00
150μF ≤ C		0.85	0.90	1.00	1.00

After endurance ESR (100 kHz, -40 °C)

Size	φ5 x L5.8	φ6.3 x L5.8	φ6.3 x L7.7	φ8 x L10.2	φ10 x L10.2
ESR (Ω)	2	1.4	0.8	0.4	0.3

Guidelines and precautions regarding the technical information and use of our products described in this online catalog.

- If you want to use our products described in this online catalog for applications requiring special qualities or reliability, or for applications where the failure or malfunction of the products may directly jeopardize human life or potentially cause personal injury (e.g. aircraft and aerospace equipment, traffic and transportation equipment, combustion equipment, medical equipment, accident prevention, anti-crime equipment, and/or safety equipment), it is necessary to verify whether the specifications of our products fit to such applications. Please ensure that you will ask and check with our inquiry desk as to whether the specifications of our products fit to such applications use before you use our products.
- The quality and performance of our products as described in this online catalog only apply to our products when used in isolation. Therefore, please ensure you evaluate and verify our products under the specific circumstances in which our products are assembled in your own products and in which our products will actually be used.
- If you use our products in equipment that requires a high degree of reliability, regardless of the application, it is recommended that you set up protection circuits and redundancy circuits in order to ensure safety of your equipment.
- The products and product specifications described in this online catalog are subject to change for improvement without prior notice. Therefore, please be sure to request and confirm the latest product specifications which explain the specifications of our products in detail, before you finalize the design of your applications, purchase, or use our products.
- The technical information in this online catalog provides examples of our products' typical operations and application circuits. We do not guarantee the non-infringement of third party's intellectual property rights and we do not grant any license, right, or interest in our intellectual property.
- If any of our products, product specifications and/or technical information in this online catalog is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially with regard to security and export control, shall be observed.

<Regarding the Certificate of Compliance with the EU RoHS Directive/REACH Regulations>

- The switchover date for compliance with the RoHS Directive/REACH Regulations varies depending on the part number or series of our products.
- When you use the inventory of our products for which it is unclear whether those products are compliant with the RoHS Directive/REACH Regulation, please select "Sales Inquiry" in the website inquiry form and contact us.

We do not take any responsibility for the use of our products outside the scope of the specifications, descriptions, guidelines and precautions described in this online catalog.
