



| LOC | DIST | REVISIONS | | | | |
|-----|------|-----------|-----|--------------------------|-----------|-----|
| | | P | LTR | DESCRIPTION | DATE | DWN |
| — | — | | H | UPDATE PER ECO-11-013056 | 23 JUN 11 | CAS |

- 1 CONNECTOR BODY AND COUPLING NUT MATERIAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138 OR POLYPHENYLENE SULFIDE (PPS) PER ASTM D4067
O-RING MATERIAL: FLUOROSILICONE
- 2 WIRE TERMINATION: 28 AWG SOLID, 30 AWG STRANDED WIRE OR SMALLER
- 3 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 4 THIS DRAWING ALSO IDENTIFIED AS NANONICS 303-0032

| | | | | | | | |
|---|--|--|--|---|--|---|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN M. STORRY 27 MAY 99 | |  TE Connectivity | | | |
| | | CHK E. PAULUS 11 JUN 99 | | | | | |
| DIMENSIONS: INCHES | | TOLERANCES, UNLESS OTHERWISE SPECIFIED: | | APVD S. KAIN 27 JAN 00 | | NAME | |
|  | | 0 PLC ± - | | PRODUCT SPEC | | PLUG ASSEMBLY, CIRCULAR, THREADED COUPLING, METAL, 7 POSITION | |
| | | 1 PLC ± - | | — | | | |
| | | 2 PLC ± .010 | | APPLICATION SPEC | | | |
| | | 3 PLC ± .005 | | — | | | |
| 4 PLC ± - | | ANGLES ± 1° | | SIZE | | RESTRICTED TO | |
| MATERIAL | | FINISH | | WEIGHT — | | A2 | |
| SEE NOTES | | SEE NOTES | | CUSTOMER DRAWING | | CAGE CODE 0PJN9 | |
| | | | | | | DRAWING NO C=1589063 | |
| | | | | | | SCALE 6:1 | |
| | | | | | | SHEET 1 of 1 | |
| | | | | | | REV H | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[TCM007PC2DC012](#)