

## Coaxial PCB Connector 82\_MBX-50-0-4/113\_N

### Description

Straight PCB jack

Interface Standards  
HUBER+SUHNER MBX



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	6 GHz

#### Mechanical Data

Board mounting type	through holes
Weight	0.001714 kg

#### Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	LCP (Liquid crystal polymer)	

### Related Documents

Outline drawing	DOU-00144735
Catalogue drawing	DCA-00161472
Mounting hole	DPA-00144881

### Ordering Information

Tape and Reel package	82_MBX-50-0-4/113_NM
Bulk 100 pcs package	82_MBX-50-0-4/113_NH
Single package	82_MBX-50-0-4/113_NE

### Remarks

PCB connector with stand-offs

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[82\\_MBX-50-0-4/113\\_NM](#) [82\\_MBX-50-0-4/113\\_NH](#) [82\\_MBX-50-0-4/113\\_NE](#)