

I/O module - IBS IP CDIO/R 24-8/SF - 2719564

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Digital input/output module, for use on robots, IP65 protection, 8 inputs, 24 V DC, 4-wire connection technology or 8 outputs, 24 V DC, 0.5 A, 3-wire connection technology, connection of additional signals on the back of the module

The illustration shows version IBS IP CDIO/R 24-8

Product Description

The IBS IP CDIO/R 24... modules are available as an input/output unit for the robot concept. The metal housing allows them to be used in welding applications. The module can be used directly on the welding transformer if it is mounted on a terminal box. The modules are connected via a 17-pin circular connector. In addition to the INTERBUS and power supply lines, this connector also carries two further signal lines for constant current regulation (CCR) and for secondary circuit monitoring (SCM). These signals are looped in on the underside of the .../SF devices and are needed at the welding current controller for control and monitoring tasks.

Two module types are available:

The IBS IP CDIO 24-8 ... module has 8 channels that can be used either as inputs or as outputs.

The IBS IP CDIO 24-12/4/8 ... module has 12 inputs and 8 outputs.

Product Features

- IP65 degree of protection
- Electrical isolation of I/O and bus logic



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	681.0 g
Custom tariff number	85176200
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	54 mm
-------	-------

I/O module - IBS IP CDIO/R 24-8/SF - 2719564

Technical data

Dimensions

Height	150 mm
Depth	62 mm

Ambient conditions

Degree of protection	IP65
----------------------	------

Interfaces

Interface	Installation remote bus
-----------	-------------------------

Power supply

Residual ripple	3.6 V _{PP}
-----------------	---------------------

Inputs

Number of inputs	8
Connection method	4-wire
Input voltage	24 V DC
Input voltage range "0" signal	-30 V ... 5 V
Input voltage range "1" signal	13 V ... 30 V

Outputs

Number of outputs	7
Connection method	3-conductor (shielded)
Type of protection	Short-circuit protection, polarity reversal protection

General

Weight	800 g
--------	-------

Classifications

eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250302
eCl@ss 5.0	27250302
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604
eCl@ss 9.0	27242604

ETIM

ETIM 2.0	EC001430
----------	----------

I/O module - IBS IP CDIO/R 24-8/SF - 2719564

Classifications

ETIM

ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Circular connector (cable-side)

Cable connector - TGGM/CDIO/17-ST - 1667895

INTERBUS remote bus connectors, straight, with contacts 12x 1597862, 5x 1602996, with IP68 cable gland Pg16, pin contact insert

I/O module - IBS IP CDIO/R 24-8/SF - 2719564

Accessories

Cable connector - TGGM/CDIO/17-BU - 1667905



INTERBUS remote bus connector, straight, with contacts 12x 1599600, 5x 1602998, with IP68 cable gland Pg16, socket contact insert

Cable connector - TWGM/CDIO/17-ST - 1667950



INTERBUS remote bus connector, angled, with contacts, male contact insert

Cable connector - TWGM/CDIO/17-BU - 1667963



INTERBUS remote bus connector, angled, with contacts, female contact insert

Protective cap

Protective cap - MSK 2 - 1665907




M23 metal sealing cap, for unoccupied M23 connectors, with steel wire

Drawings


I/O module - IBS IP CDIO/R 24-8/SF - 2719564

Dimensional drawing



I/O module - IBS IP CDIO/R 24-8/SF - 2719564

Connection diagram



a = female n

b = male n+1

c = sensor sockets 1, 3, 5, 7

d = sensor sockets 2, 4, 6, 8

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

2719564