




PART NUMBER	ENGINEERING NO.	LENGTH ± TOLERANCE
1201080050	EWWA06215M010	3' 3" +2.19"/-0" [1M +55.6/-0 mm]
1201080052	EWWA06215M050	16' 4" +6.5"/-0" [5M +165.0/-0 mm]

AUX VIEW
SCALE 1:4



NOTES:

- 1) MATERIAL: SEE TABLE
- 2) FINISHES: SEE TABLE
- 3) CABLE: #26/4 SHIELDED PVC
- 4) ELECTRICAL DATA:
ACCORDING TO CAT5e ETHERNET STANDARD
MAX. VOLTAGE: 30V
MAX. CURRENT 1.5A



MALE- FACE VIEW



WIRING DIAGRAM

- 5) ENVIRONMENTAL:
PROTECTION IP67
TEMPERATURE RANGE: -20°C TO 75°C
- 6) WRAP LABEL IS MARKED WITH P/N, DATE CODE,
VOLTAGE & AMPERAGE.
- 7) ASSEMBLY IS RoHS COMPLIANT.

6	1	LABEL	PLASTIC FILM	BLACK/YELLOW
5	2	INSERT	PUR	BLACK
4	8	PIN CONTACT	COPPER ALLOY	GOLD PLATED
3	2	M12 ULTRA-LOCK HEAD ASSY	BRASS	NICKEL
2	2	OVERMOLD	PUR	BLACK
1	1	ETHERNET CABLE-CAT5E	PVC JACKET	TEAL
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

SD RELEASE	7/7/09	1	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE IN/MM	SCALE 3:4	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
EC NO: WEU2010-0005	DRWNR: VOU	CHKD: BWOODMAN	APPR: JFMURPHY	4 PLACES mm ±----	4 PLACES INCH ±----	DRAWN BY VOU	DATE 2009/07/07	TITLE M12 ULOCK CABLE ASSY 4P M/MP ST/90 D-CODE #26/4 SHIELDED PVC
			DESCRIPTION	3 PLACES mm ±----	3 PLACES INCH ±.005	CHECKED BY BWOODMAN	DATE 2009/07/31	
				2 PLACES mm ±----	2 PLACES INCH ±.010	APPROVED BY	DATE	
				1 PLACE mm ±----	1 PLACE INCH ±.020	molex	MOLEX INCORPORATED	
				ANGULAR ±1/2°		MATERIAL NO.	DOCUMENT NO.	
				DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART	SD-120108-005	SHEET NO. 1 OF 1
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH	SIZE A	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex](#):

[1201080051](#)