




**TW SERIES**

THROUGH-HOLE BOARD STACKERS



TW

NO. PINS PER ROW

LEAD STYLE

PLATING OPTION

ROW OPTION

STACKER HEIGHT

TAIL SPEC

02 thru 50

Specify
LEAD STYLE
from chart below.

-F
= Gold flash on post,
Matte Tin on tail

-L
= 10 μ " (0.25 μ m)
Gold on post,
Matte Tin on tail

-T
= Matte Tin

-S
= Single Row

-D
= Double Row

-T
= Triple Row

-Q
= Four Row

-5
= Five Row

-6
= Six Row

- "XXX"
= Stacker Height in inches (0.13 mm) .005" increments
Example: -.250 = (6.35 mm) .250"

- "XXX"
= Tail Length in inches (0.13 mm) .005" increments
Example: -.150 = (3.81 mm) .150"

Diagram illustrating the standard lead style dimensions and options. The lead style is shown with dimensions: 04, 01, .0787 TYP, .020 SQ, .0787, 300, 295, No. of rows X (2.00) .0787, -S, -D*, -Q, -T, -5, -6.

Diagram illustrating the stacker height lead style dimensions and options. The lead style is shown with dimensions: POST, TAIL, .051, .020 SQ, .0787, .050 MIN, .127, STACKER HEIGHT See Chart, OAL, -S, -D*, -Q, -T, -5, -6.

LEAD STYLE	OAL
-01	(8.20) .323
-02	(9.60) .377
-03	(13.60) .535
-04	(14.10) .555
-05	(15.10) .594
-06	(17.10) .673
-07	(19.10) .751
-08	(21.10) .830
-09	(11.60) .456
-10	(15.60) .614
-11	(10.08) .397
-12	(28.19) 1.110

* Style -08 & -12 = S & D only

ROW OPTION	STACKER HEIGHT
-S, -D*, & -Q	(3.05) .120 MIN
-T, -5, -6	(4.06) .160 MIN

* -D with stacker height greater than (4.06 mm) .160" will not have standoffs.

Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[TW-25-02-L-D-130-100](#)