

PANDUIT PART NO. *	USED WITH CABLE TIES	HOLE SIZE in (mm)	WEIGHT lbs/ 100 pc (g)/
SGMPMWH32	M, I, S, LH, H SG100M, SG150I, SG200S, SG250S, SG300S, SG370S, SG350LH, SG450H	.315 DIA. X 1.41 DP (8 DIA. X 35.8 DP)	0.67 (303)
MPMWH32			

* 1. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE.

										DIMENSIONS IN BRACKETS ARE METRIC [mm]	
										CAD FILENAME/LAYERS	
										G00201BA_PB_MPMWH32_05	
											
										CORP. TINLEY PARK, ILLINOIS	
										SUPER GRIP MASONARY PUSH MOUNT	
										SGMPMWH32 & MPMWH32	
										UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:	
										(.X) ± 0.1 (2.5) (.XXX) ± 0.020 (.5) (.XX) ± 0.05 (1.3) ANGLES ± 5°	
										UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.	
										DRAWN BY TMSA	
										DATE 5-23-06	
										MAT'L:	
										IMPACT RESISTANT WEATHER RESISTANT NYLON 6/6 COLOR: BLACK	
										SCALE FULL	
										DRAWING NO. G00201BA	
										DWG A SIZE	
5	5-23-06			COMPLETELY REVISED LAYOUT AND ADDED PART NUMBER SGMPMWH32			GB0201BA	5			
REV	DATE	BY	CHK	DESCRIPTION			ECN	- R	CUST	SUP	QC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[MPMWH32-D0](#) [SGMPMWH32-L0](#)