

PART NUMBER SSI-LXMP059AD

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	ADDED DIMS, NOTES AND UPDATED SPECS.	12.19.94
В	E.C.N. #10122.	6.27.96
С	E.C.N. #10BRDR. & REDRAWN IN 3D.	1.7.02

ELECTRO-OPTICAL	CHARACTERI	STICS TA=25°	'C	$I_f = 20mA$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		605		nm	
FORWARD VOLTAGE		2.0	2.5	۷f	
REVERSE VOLTAGE	5.0			٧r	1 _r =100,uA
AXIAL INTENSITY		5		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		110		2x theta	
EMITTED COLOR:	AMBER				
EPOXY LENS FINISI	H: AMBER	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/'C
OPERATING, STORAGE TEMP.	$-40\ T0\ +85$	°C
SOLDERING TEMP.	+ 260	° C
2.0mm FROM BODY		3 SEC. MAX

* t<10µS

NOTES:

- 1. SSL-LX2573AD, AMBER LED.
- 2. SSH-LXMP059-HSG, BLACK HOUSING.
- 3. SSH-LXMP059-BSG, BLACK BUSHING.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.039). MIN= +DECIMAL PRECISION -0.00

REV. PART NUMBER SSI-LXMP059AD 605nm AMBER RECTANGULAR PANEL INDICATOR.

AMBER DIFFUSED LENS.

CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

1,25~3,00 [0,049~0,118]

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

APPROVED BY: DATE: DRAWN BY: CHECKED BY: 9.30.92 PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSI-LXMP059AD