



| SHELL | A±0.38 | B±0.12 | C±0.10 | D±0.25 | E±0.07 | G±0.25 | PART NUMBER | |
|-------|--------|--------|--------|--------|--------|--------|----------------|----------------|
| 09 | 30.81 | 24.99 | 16.96 | 16.79 | 10.96 | 5.90 | D09P33E4GX00** | D09P33E6GX00** |
| 15 | 39.14 | 33.32 | 25.18 | 25.12 | 19.18 | 5.90 | D15P33E4GX00** | D15P33E6GX00** |
| 25 | 53.03 | 47.04 | 39.12 | 38.84 | 33.12 | 5.70 | D25P33E4GX00** | D25P33E6GX00** |
| 37 | 69.32 | 63.50 | 55.68 | 55.30 | 49.68 | 5.70 | D37P33E4GX00** | D37P33E6GX00** |

Gold flash 0.76µ gold

LF FOR LEAD FREE

PC card drilling dimensions(after plating)
(thickness 1.60±0.20mm)

GENERAL CHARACTERISTICS : SEE DRAWING C01-8646-0000

| | | | | | | | | | |
|-------------|-------------|------------|------------|---------------------------------------|----------|------------|--|-----------------------------------|--|
| mat'l. code | | surface | | tolerance | | projection | | product family | |
| - | | ISO 1302 ✓ | | ISO 406 ISO 1101 | | | | D-SUB | |
| ltr | ecn no | dr | date | tolerances unless otherwise specified | | | | title | |
| D | ELX-I-18691 | AB | 2014-07-29 | angles | .0±0.1 | MM | | MALE CONNECTOR DD RIGHT ANGLED | |
| E | ELX-I-30554 | GM | 2018-06-27 | linear | .00±0.1 | ← | | with nut, harpoon and metal plate | |
| | | | | 0°±1' | .000±0.1 | scale 2:1 | | dwg no | |
| | | | | dr JOHN SLEEBA 1997-10-27 | | | | sheet 1 of 1 size | |
| | | | | engr MITHUN PAUL 2014-07-29 | | | | C01-8646-0826 A3 | |
| | | | | chr GREGAR M 2018-06-27 | | | | type Product Customer Drawing | |
| | | | | appr BIJU K PAUL 2018-06-27 | | | | | |
| sheet index | revision | E | | | | | | | |
| | sheet | 1 | | | | | | | |