



ST-200

GRAY
WIRING

TIP - CENTER CONDUCTOR
SLEEVE - SHIELD

22 AWG STRANDED, CENTER
CONDUCTOR, SPIRAL SHIELD,
0.155 OD PVC GRAY

ST-200

GRAY
WIRING

TIP - CENTER CONDUCTOR
SLEEVE - SHIELD

NOTES:

- MATERIALS:**
TIP - BRASS, NICKEL PLATED
SLEEVE - BRASS, NICKEL PLATED
INSULATION - PHENOLIC AND POLYESTER
INTERNAL SHIELD - STEEL, TIN PLATED
MOLDED HANDLE - THERMOPLASTIC, GRAY

2. THIS PRODUCT IS RoHS COMPLIANT.

05 **A** * **05** **X**
 RoHS COMPLIANT
 2ND END - ST-200
 CABLE LENGTH PER TABLE BELOW
 B = 12 INCHES LONG
 C = 18 INCHES LONG
 D = 24 INCHES LONG
 F = 36 INCHES LONG
 H = 48 INCHES LONG
 K = 6 FEET LONG
 N = 10 FEET LONG
 R = 15 FEET LONG
 U = 25 FEET LONG
 TYPE OF CABLE - W1000 - 1
 1ST END - ST-200

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					SIZE	WIDTH	MULT	LBS/M	TEMPER	
					FINISH			MATERIAL		
					SPEC No.			SPEC No.		
					FIRST USED ON		SCALE 1:1			
					DATE DRAWN	BY	CHKD	APVD		
					9-11-06	RF	RF	TJK		
					9-11-06		8-13-09			
					NAME				PART No.	REV
					CABLE ASSEMBLY				05A_05X	A
					ST-200 TO ST-200, RoHS					
UNLESS OTHERWISE SPECIFIED										
1. ALL DIMENSIONS IN INCHES										
- TWO PLACE DECIMALS ±0.02										
- THREE PLACE DECIMALS ±0.005										
A	26124	8-9-06	JEB	TJK						
REV	ECO NUMBER	DATE	BY	APVD						
REVISIONS					DO NOT SCALE DRAWING					

SolidWorks CAD File

