



.065	1.65	-	-
.063	1.60	-	-
.060	1.52	-	-
.045	1.14	-	-
.030	0.76	1.000	25.40
.018	0.46	.700	17.78
.015	0.38	.450	11.43
.012	0.30	.250	6.35
.010	0.25	.156	3.96
.008	0.20	.140	3.56
.005	0.13	.125	3.18
.003	0.08	.078	1.98
.001	0.03	.070	1.78
IN	MM	IN	MM

CONVERSION TABLE

RECOMMENDED MOUNTING HOLE PATTERN FOR .063 THICK P.C. BOARD

- 1 POST TO WITHSTAND 13 NEWTONS (3LBS.) MIN. AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- 2 TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- 3 MEASURED AT SURFACE -A-
- 4 PLASTIC FLASH PERMITTED IN THIS AREA.
- 5 PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- 6 ONE HOLE MAY BE UNDERSIZED (.065/.060 DIA.) FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- 7 MATERIAL: HEADER-THERMOPLASTIC POLYESTER GLASS-FILLED 94V-0(NATURAL) POST-COPPER ALLOY (TIN PLATED)
- 8 COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9 PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- 10 POST TO BE MEASURED WHEN STRIP IS HELD FLAT.
- 11 POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- 12 DIMENSION SHOULD BE .140 MIN WHEN MATING WITH A MTA 156 CONNECTOR ASSEMBLY OR A SL-156 CONNECTOR ASSEMBLY.
- 13 PIN BURR OF .005 MAX. VERTICAL AND .003 MAX. HORIZONTAL PERMITTED AT POST TIPS ON BOTH ENDS.
- 14 PRELIMINARY- NOT FOR PRODUCTION

NONE	3rd	2.028	51.51	13	3-640383-1
		3.744	95.10	24	2-640383-4
		3.588	91.14	23	2-640383-3
		3.432	87.17	22	2-640383-2
		3.276	83.21	21	2-640383-1
		3.120	79.25	20	2-640383-0
		2.964	75.29	19	1-640383-9
		2.808	71.32	18	1-640383-8
		2.652	67.36	17	1-640383-7
		2.496	63.40	16	1-640383-6
		2.340	59.44	15	1-640383-5
		2.184	55.47	14	1-640383-4
		2.028	51.51	13	1-640383-3
		1.872	47.55	12	1-640383-2
	1.716	43.59	11	1-640383-1	
	1.560	39.62	10	1-640383-0	
	1.404	35.66	9	640383-9	
	1.248	31.70	8	640383-8	
	1.092	27.74	7	640383-7	
	.936	23.77	6	640383-6	
	.780	19.81	5	640383-5	
	.624	15.85	4	640383-4	
	.468	11.89	3	640383-3	
	.312	7.92	2	640383-2	
OMIT POS.	IN	MM	NUMBER OF POSITIONS	PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN B. LEWIS 10-14-92	TE Connectivity
0. PLC ± -	1. PLC ± -	CHK R. SWING 10-14-92	MTA-156 HEADER ASSEMBLY, PLAIN, STRAIGHT, .045 SQUARE POST, TIN PLATED
2. PLC ± -	3. PLC ± .005	APVD -	SIZE CASE CODE DRAWING NO. RESTRICTED TO
4. PLC ± -	ANGLES ± -	PRODUCT SPEC -	A1 00779 640383
MATERIAL 7	FINISH 7	APPLICATION SPEC -	WEIGHT -
CUSTOMER DRAWING		SCALE 5:1	SHEET 1 OF 1 REV AA1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[640383-2](#)