


AIMB-273

**Intel® Core™ i7/i5/i3/Celeron
uFC-PGA988 Mini-ITX with 2 DP/HDMI/
LVDS/CRT, 2 COM, Dual LAN, PCIe x16**



iManager WISE-PaaS/RMM **CE FCC**

Features

- Supports Intel® Core™ i7/i5/i3 mobile processor (PGA) with Intel QM77 chipset
- Two 204-pin SO-DIMM up to 16 GB DDR3 1333/1600 MHz SDRAM
- Supports triple display of 2 DP, HDMI, LVDS, CRT
- Supports PCIe x16 (Gen 3) and mini PCIe
- Supports Intel vPro, AMT 8.0, PECI 3.0, Software RAID 0,1,5,10, TPM 1.2 (optional)
- Supports iManager, WISE-PaaS/RMM and Embedded Software APIs

Software APIs:




Utilities:



Specifications

Processor System	CPU	Intel Core i7-3610QE	Intel Core i7-2710QE	Core i5-3610ME	Core i5-2510E	Core i3-3120ME	Core i3-2330E	Celeron B810
	Core Number	4	4	2	2	2	2	2
	Max Speed	2.3 GHz	2.1 GHz	2.7GHz	2.5 GHz	2.4 GHz	2.2 GHz	1.6 GHz
	L3 Cache	6 MB	6 MB	3MB	3 MB	3MB	3 MB	2 MB
	Chipset	QM77						
Expansion Slot	BIOS	AMI EFI 64 Mbit SPI						
	PCI	-						
	Mini-PCIe	1						
	PCIe x16 (Gen3)	16 GB/s per direction, 1 slot						
Memory	Technology	Dual Channel DDR3 1333/1600 MHz SDRAM						
	Max. Capacity	16 GB/8 GB per SO-DIMM						
	Socket	2 x 204 PIN DDR3 SO-DIMM						
Graphics	Controller	Integrated Gfx Gen 7, supports DirectX11, OpenGL 3.1 and OpenCL 1.1						
	VRAM	Shared system memory, 2 GB and above, total system memory shared 1 GB maximum video memory						
	CRT	Yes, supports max. resolution 2048 x 1536						
	LVDS	Supports dual channel 48 bit up to 1920 x 1080						
	HDMI	Supports HDMI 1.4, 1650 Mbps/channel with 165 MHz						
Ethernet	Triple Display	DP+LVDS+HDMI, DP+DP+HDMI, DP+DP+LVDS, DP+CRT+HDMI (The Celeron B810 processor doesn't support triple display)						
	Interface	10/100/1000 Mbps						
	Controller	GbE LAN1: Intel 82579LM, LAN2: Intel 82583V						
SATA	Connector	RJ-45 x 2						
	Max Data Transfer Rate	600 MB/s (SATA 3.0)/ 300 MB/s (SATA 2.0)						
Rear I/O	Channel	2/2						
	CRT	1						
	HDMI	1						
	Display Port	2						
	Ethernet	2						
	USB	4 (USB 3.0)						
	Audio	3 (Mic-in, Line-out, Line-in)						
	Serial	-						
	PS/2	2 (1 x keyboard and 1 x mouse)						
	USB	4 (USB 2.0)						
	LVDS/Inverter	1						
Internal Connector	Serial	2 (RS-232, COM2 with 5 V/12 V)						
	IDE	-						
	SATA	2 (SATA 3.0), 2 (SATA 2.0)						
	Mini-PCIe	1						
	CFast	1						
	Parallel	-						
	IrDA	-						
	GPIO	8-bit						
Watchdog Timer	Output	System reset						
	Interval	Programmable 1 ~ 255 sec/min						
Power Requirements	Power On	Intel Core i7 -3610QE 2.30GHz processor/DDR3-1333MHz 4G x2/16G SQFlash						
	5 V	3.3 V	12 V		5 Vsb		-12 V	
	3.42 A	1.1 A	1.19 A		0.5 A		0.07A	
Environment	Operating	Non-Operating						
	Temperature	0 ~ 60° C (32 ~ 140° F), depends on CPU speed and cooler solution						
Physical Characteristics	Dimensions	-40 ~ 85° C (-40 ~ 185° F)						
	Dimensions	170 mm x 170 mm (6.69" x 6.69")						

Block Diagram



Ordering Information

Part Number	Chipset	DP	CRT	LVDS	HDMI	GbE LAN	COM
AIMB-273G2-00A1E	QM77	2	1	1	1	2	2

Packing List

Part Number	Description	Quantity
1700003194	SATA HDD cable	2
1703150102	SATA power cable	2
1960051292N001	CPU cooler	1
1960019192T100	I/O port bracket	1
20060273010	Startup manual	1

I/O View



AIMB-273G2-00A1E

Optional Accessories

Part Number	Description
1700003195	USB cable with two ports, 17.5 cm
1700002204	USB cable with two ports, 27 cm
1700008461	USB cable with four ports, 30.5 cm

Optional Chassis

Part Number	Description
AIMB-B2000-15ZE	Mini-ITX chassis with 150W ATX power supply

Embedded OS/API

OS/API	Part number	Description
Win XPE	2070011021	XPE WES 2009
WES7	2070011359	Windows 7 Embedded English version
WES7E	2070011440	WES7E JPN/TC/SC/ENG

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advantech:](#)

[AIMB-273G2-00A1E](#)