

TINA-RS

~13° spot beam optimized for CREE XP-E. Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Dimensions Ø 16.1 mm

Height 9.7 mm

Fastening tape

Colour white

Box size 470 x 240 x 105 mm

Box weight 4 kg

Quantity in Box 2016 pcs


ROHS compliant yes 1



MATERIAL SPECIFICATIONS:

Component	Туре	Material	Colour
TINA-XP-RS	Lens	PMMA	clear
TINA-XP-H-TAPE-WHT	Holder	PC	white
TINA-TAPE3	Tape	PU tape	black





PHOTOMETRIC DATA (MEASURED):

CREE 💠


LED XP-E

FWHM 10.0°

Efficiency 93 %

Peak intensity 18.300 cd/lm

Required components:



CREE \$


LED XP-G

FWHM 15.0° Efficiency 94 %

Peak intensity 11.100 cd/lm

Required components:





PHOTOMETRIC DATA (SIMULATED):


CREE 💠

LED XD16 FWHM 12.0°

Efficiency 92 %

Peak intensity 13.170 cd/lm

Required components:




CREE 🕏

LED XP-G3 FWHM 16.0°

Efficiency 87 %

Peak intensity 7.300 cd/lm

Required components:



SEOUL SEMICONDUCTOR

LED Z5

FWHM 11.0° Efficiency %

Peak intensity cd/lm

Required components:


SEOUL SEMICONDUCTOR

LED Z5M1/Z5M2

FWHM 14.0° Efficiency 94 %

Peak intensity 10.790 cd/lm

Required components:





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

FA10887_TINA-RS