XESP20215

limit switch contact block XESP - 2C/O snap action, simultaneous - silver plated



Product availability: Non-Stock - Not normally stocked in distribution facility



Main Commercial Status Commercialised Range of product OsiSense XC Series name Standard format Product or component Limit switch contact block type Device short name XESP Associated body ZCKJ25 Number of poles Contacts operation Snap action, simultaneous Contacts type and 2 C/O composition

Complementary

Product compatibility	XCKJ
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.752 x 1.5 mm ²
Contacts insulation form	Za
Contacts material	Silver plated contacts
Positive opening	Without
Minimum actuation speed	0.01 mm/s
Resistance across terminals	< 25 mOhm conforming to IEC 60255-7 category 3
Electrical durability	5000000 cycles, DC-13 48 V, 7 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 24 V, 10 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 cycles, DC-13 120 V, 4 W, operating rate: < 60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C

Ordering and shipping details

Category	22449 - LIMIT SWITCHES, ACCESSORIES	
Discount Schedule	Т	
GTIN	003389118129047	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.04	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	Υ	
Country of origin	FR	

Offer Sustainability

Green Premium product
Compliant - since 1149 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold
Available Download Product Environmental
Need no specific recycling operations

Period 18 months



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XESP20215