



RECOMMENDED HOLE LAYOUT

- 1 STANDOFFS:  
3 THRU 9 POSN - (2 REQD) ON OUTSIDE ENDS OF HOUSING  
10 THRU 18 POSN - (3 REQD) TWO ON OUTSIDE ENDS AND ONE CENTERED ON HOUSING  
19 POSN AND LARGER - (4 REQD) TWO ON OUTSIDE ENDS AND TWO EVENLY SPACED WITHIN REMAINING LENGTH OF HOUSING
- 2 RECESSED DATE CODE
- 3 FOR 3 POSITION ONLY, ONE SLOT .215 WIDE.
- 4 .000100-.000200 BRIGHT TIN-LEAD OVER .000050 NICKEL.
- 5 .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
- 6 PRELIMINARY PART
- 7 .000100-.000200 MATTE TIN OVER .000050 NICKEL.
- 8 MATERIAL:  
HOUSING: FLAME RETARDANT THERMOPLASTIC, COLOR: BLACK  
POSTS: PHOS BRONZE
- 9 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

FINISH	D	C	B	A	NO. OF POSN	PART NO.
△	2.620	2.540	2.400	24	25	7-102523-3
△	2.520	2.440	2.300	23	24	7-102523-2
△	2.420	2.340	2.200	22	23	7-102523-1
△	2.320	2.240	2.100	21	22	7-102523-0
△	2.220	2.140	2.000	20	21	6-102523-9
△	2.120	2.040	1.900	19	20	6-102523-8
△	2.020	1.940	1.800	18	19	6-102523-7
△	1.920	1.840	1.700	17	18	6-102523-6
△	1.820	1.740	1.600	16	17	6-102523-5
△	1.720	1.640	1.500	15	16	6-102523-4
△	1.620	1.540	1.400	14	15	6-102523-3
△	1.520	1.440	1.300	13	14	6-102523-2
△	1.420	1.340	1.200	12	13	6-102523-1
△	1.320	1.240	1.100	11	12	6-102523-0
△	1.220	1.140	1.000	10	11	5-102523-9
△	1.120	1.040	.900	9	10	5-102523-8
△	1.020	.940	.800	8	9	5-102523-7
△	.920	.840	.700	7	8	5-102523-6
△	.820	.740	.600	6	7	5-102523-5
△	.720	.640	.500	5	6	5-102523-4
△	.620	.540	.400	4	5	5-102523-3
△	.420	.340	.200	2	3	5-102523-2
△	.520	.440	.300	3	4	5-102523-1
△	1.120	1.040	.900	9	10	3-102523-7
△	.920	.840	.700	7	8	3-102523-6
△	.520	.440	.300	3	4	3-102523-5
△	3.720	3.640	3.500	35	36	3-102523-4
△	3.620	3.540	3.400	34	35	3-102523-3
△	3.520	3.440	3.300	33	34	3-102523-2
△	3.420	3.340	3.200	32	33	3-102523-1
△	3.320	3.240	3.100	31	32	3-102523-0
△	3.220	3.140	3.000	30	31	2-102523-9
△	3.120	3.040	2.900	29	30	2-102523-8
△	3.020	2.940	2.800	28	29	2-102523-7
△	2.920	2.840	2.700	27	28	2-102523-6
△	2.820	2.740	2.600	26	27	2-102523-5
△	2.720	2.640	2.500	25	26	2-102523-4
△	2.620	2.540	2.400	24	25	2-102523-3
△	2.520	2.440	2.300	23	24	2-102523-2
△	2.420	2.340	2.200	22	23	2-102523-1
△	2.320	2.240	2.100	21	22	2-102523-0
△	2.220	2.140	2.000	20	21	1-102523-9
△	2.120	2.040	1.900	19	20	1-102523-8
△	2.020	1.940	1.800	18	19	1-102523-7
△	1.920	1.840	1.700	17	18	1-102523-6
△	1.820	1.740	1.600	16	17	1-102523-5
△	1.720	1.640	1.500	15	16	1-102523-4
△	1.620	1.540	1.400	14	15	1-102523-3
△	1.520	1.440	1.300	13	14	1-102523-2
△	1.420	1.340	1.200	12	13	1-102523-1
△	1.320	1.240	1.100	11	12	1-102523-0
△	1.220	1.140	1.000	10	11	1-102523-9
△	1.120	1.040	.900	9	10	102523-8
△	1.020	.940	.800	8	9	102523-7
△	.920	.840	.700	7	8	102523-6
△	.820	.740	.600	6	7	102523-5
△	.720	.640	.500	5	6	102523-4
△	.620	.540	.400	4	5	102523-3
△	.420	.340	.200	2	3	102523-2
△	.520	.440	.300	3	4	102523-1

△ SUP BY 6-102523-4

THIS DRAWING IS A CONTROLLED DOCUMENT. DIN S.A. SHUEY 28SEP89

APVD H.MOLL 30CT89

CHK R.ELICKER 30CT89

NAME

PRODUCT SPEC

APPLICATION SPEC

SIZE CASE CODE DRAWING NO. RESTRICTED TO

WEIGHT

A1 00779 102523

CUSTOMER DRAWING SCALE 4:1 SHEET 1 OF 1 REV R2

TE Connectivity

HEADERR ASSEMBLY MOD II, SINGLE ROW .100 C/L, RIGHT ANGLE

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5-102523-8](#)