

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0755615100](#)
Status: **Active**
Overview: [EXTreme PowerMass High-Current Connectors](#)
Description: EXTreme PowerMass 0.13mm Pitch, 40A per module, 1 Circuit, Right-Angle Plug, Lower Blade Sub Assembly, Tail Length 3.07mm, without Pegs

Documents:

[3D Model](#) [Packaging Specification PK-46081-100-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification


CSA LR19980
UL E29179

General

Product Family PCB Headers
Series [75561](#)
3D Viewer Yes
Application Board-to-Board, Power
CURRENT-MAX-NUMERIC 40.0
Comments 40A per contact, 40A per contact
Overview [EXTreme PowerMass High-Current Connectors](#)
PITCH-MATING-NUMERIC 3.00
Product Name EXTreme PowerMass
UPC 800756779461

Physical

(p)ower-(s)ignal Configuration 1p - 0s
Breakaway No
Circuits (Loaded) 2
Circuits (maximum) 4
Durability (mating cycles max) 50
First Mate / Last Break No
Flammability 94V-0
Glow-Wire Capable No
Guide to Mating Part No
Keying to Mating Part None
Lock to Mating Part No
Material - Metal Copper-Nickel-Silicon
Material - Plating Mating Gold
Material - Plating Termination Tin
Net Weight 7.740/g
Number of Rows 2
Orientation Right Angle
PC Tail Length 3.07mm
PCB Locator No
PCB Retention None
PCB Thickness - Recommended 2.40mm
Packaging Type Tray
Pitch - Mating Interface 3.00mm
Plating min - Mating 0.762µm
Plating min - Termination 2.540µm
Polarized to Mating Part Yes
Polarized to PCB Yes
Shrouded Closed Ends
Stackable No
Surface Mount Compatible (SMC) Yes



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
ED/71/2019 (16 July
2019)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[75561](#) Series

Mates With

[755455000](#) EXTreme PowerMass
Receptacle, [755455001](#) EXTreme
PowerMass Receptacle

Temperature Range - Operating	-40° to +105°C
Termination Interface: Style	Through Hole
Electrical	
Current - Maximum per Contact	40.0A
Voltage - Maximum	450V
Material Info	
Reference - Drawing Numbers	
Packaging Specification	PK-46081-100-001
Sales Drawing	SD-75561-101

This document was generated on 09/25/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[75561-5100](#)