

## Contact insert - HC-QA-B 10-ST/PEL - 1678923

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON terminal adapter male insert, B10 series, 10-pos., protective conductor connection on the left for the right side of the control cabinet, QUICKON connection; contact inserts with screw, crimp, push-in and QUICKON connection can be used as mating connectors.



## **Key Commercial Data**

Packing unit	5 pc
GTIN	4 017918 168346
GTIN	4017918168346

### Technical data

### **Dimensions**

Terminal adapter width	39.5 mm
Height	34 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C

#### Electrical characteristics

Number of positions	10
Connection in acc. with standard	IEC / EN
Rated surge voltage	4 kV
Rated current	16 A

### Mechanical characteristics

Туре	B10
Connection method	QUICKON connection
Conductor cross section	0.5 mm² 1.5 mm²
Connection cross section AWG	20 16

### General



# Contact insert - HC-QA-B 10-ST/PEL - 1678923

## Technical data

### General


Note	For HEAVYCON ADVANCE panel mounting flange and HEAVYCON panel mounting base of type B10. Contact inserts with screw, crimp, and QUICKON connections can be used as mating connectors. Connectors may be operated only when there is no load/voltage.
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA / PC
Degree of pollution	3
Overvoltage category	III
Flammability rating according to UL 94	V0
Connection in acc. with standard	IEC / EN
Assembly instructions	Cannot be used for mating connectors with spring-cage and Push-in connections. If the conductor contacts again, it must be cut off above the last contact point.

### Standards and Regulations


Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

## Drawings

Dimensional drawing



### Diagram



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1678923