



Quality Products. Service Excellence.

NEMA Rated Swing-Out Wall Mount Cabinet *EN4DH Series*

Up to 180 lbs|82 kg Weight Capacity



Application

- Designed for housing network access equipment in harsh environments using 19" mounting rails.
- Dual access to both front and rear of the equipment allows easy install and connection between the main cable route and equipment.
- Provides outstanding protection against dust, oil and water with both solid and plexi-door options that carry a NEMA type 4 rating.

Standards

- **Solid Door**
 - UL 508A Type 1, 3, 3R, 4, 12
 - CSA Type 1, 3, 3R, 4, 12
- **Plexi Viewing**
 - UL 508A 1, 3, 3R, 4, 12
 - CSA Type 1, 3, 3R, 4, 12
- **Complies with**
 - NEMA type 3R, 4 and 12
 - IEC 60529 , IP54, IP66



Features

- Dual access to equipment via the double hinge design.
- Allows for 120 degrees of access to both front and rear of equipment allowing for easy maintenance.
- Heavy duty wall mounting back pan can be used for cable entry and includes collar stud provision for optional inner panel.
- Back pan can be mounted with optional external mounting feet.
- Interior latch releases the center section for added security, no tools required.
- Both solid and window door options include a combination key and padlock handle for added security.
- 1 pair tapped 10-32 L rails with cable pass through are included.
- Rails are adjustable and can be installed at your desired location.
 - Additional rails are available and sold separately.
- Bonding studs provided on door, body and back pan.

Construction

- Back pan, body and doors are made from 14 gauge steel.
- Smooth continuous welded seams without knockouts, cutouts or holes.
- Seamless poured-in place gasket for added protection in both indoor and outdoor environments.
- Window door constructed with UV resistant polycarbonate material.
- Plated L rails drilled and tapped 10-32 to EIA 19" standards.
- 25 pack of 10-32 mounting hardware is included.

Finish



- RAL7035 light gray.
- TAA Compliant.
- RoHS Compliant.
- Manufactured in North America.

Accessories

- Universal Rack Shelf
- Rack Panels
- Horizontal Lacing Strip
- Adjustable Rack Mount DIN Rail Kit
- Grounding
- Mounting Foot Kit
- 900-1300 BTU/H Indoor Air Conditioner
- Climate Control Sizing Software
- Outlet Strips
- Horizontal Hinged Cable Manager
- Horizontal Steel Finger Cable Manager
- 10-32 Mounting Hardware
- Rack Unit Label
- 17-38 CFM Filterfans
- 900-1200 BTU/H Outdoor Air Conditioner

Solid Door	Window Door	Overall Dimensions			Rack	Mounting Dimensions			Suggested Load Capacity
Part No.	Part No.	Height	Width	Depth	Units	Height	Width	Center Depth	
EN4DH162415LG	EN4DH162415WLG	16.00	24.00	15.01	7U	12.25	19.00	9.51	100 lb (45 kg)
EN4DH162424LG	EN4DH162424WLG	16.00	24.00	24.00	7U	12.25	19.00	18.50	100 lb (45 kg)
EN4DH202424LG	EN4DH202424WLG	20.00	24.00	24.00	10U	17.50	19.00	18.50	100 lb (45 kg)
-	EN4DH242415WLG	24.00	24.00	15.01	12U	21.00	19.00	9.51	120 lb (54 kg)
EN4DH242424LG	EN4DH242424WLG	24.00	24.00	24.00	12U	21.00	19.00	18.50	120 lb (54 kg)
-	EN4DH362415WLG	36.00	24.00	15.01	19U	33.25	19.00	9.51	140 lb (64 kg)
EN4DH362424LG	EN4DH362424WLG	36.00	24.00	24.00	19U	33.25	19.00	18.50	140 lb (64 kg)
EN4DH482424LG	EN4DH482424WLG	48.00	24.00	24.00	26U	45.50	19.00	18.50	180 lb (82 kg)

Optional Rear Inner Panel

Overall Dimensions		
Part No.	H	W
EPGDH1624	12.20	20.20
EPGDH2024	16.20	20.20
EPGDH2424	20.20	20.20
EPGDH3624	32.20	20.20
EPGDH4824	44.20	20.20

Optional Additional Pair of Panel Rails

Part No.	Rack Units
EPDHR7	7
EPDHR10	10
EPDHR12	12
EPDHR19	19
EPDHR26	26

Tags: Sectional Wall Mount Rack, Pivoting Rack, Data Wall Cabinet, Dual Hinge, Hinged Swing Gate, NEMA 4 Wall Cabinet, Dust-Tight Wall Mount, outdoor network enclosures

Data subject to change without notice

© 2020. Hammond Manufacturing Ltd. All rights reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hammond:

[EPDHR7](#) [EPDHR26](#) [EN4DH162415WLG](#) [EPDHR12](#) [EN4DH162415LG](#) [EPGDH2424](#) [EN4DH242424WLG](#)
[EN4DH482424WLG](#) [EPGDH4824](#) [EN4DH482424LG](#) [EN4DH242424LG](#) [EN4DH362424WLG](#) [EN4DH202415WLG](#)
[EN4DH482415LG](#)