

LOC	DIST	REVISIONS				
		REV	DATE	BY	APP'D	
CM	54	M	REVISED PER ECO-12-016930	05OCT12	KH	SM

- 1

POST TO WITHSTAND 13 NEWTONS (3LBS.) MIN. AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.
- 2

TOLERANCES APPLY TO SOLDER SIDE OF BOARD.
- 3

MEASURED AT SURFACE

-A-
- 4

PLASTIC FLASH PERMITTED IN THIS AREA.
- 5

PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.
- 6

ONE HOLE MAY BE UNDERSIZED (.065 - .060 DIA.) FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.
- 7

MATERIAL: HEADER-THERMOPLASTIC POLYESTER
GLASS-FILLED 94V-0(NATURAL)
POST-COPPER ALLOY (TIN PLATED)
- 8

COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.
- 9





PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.
- 10

POST TO BE MEASURED WHEN STRIP IS HELD FLAT.
- 11

POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.
- 12

DIMENSION SHOULD BE .175 MIN WHEN MATING WITH A MTA 156 CONNECTOR ASSEMBLY OR A SL-156 CONNECTOR ASSEMBLY.
- 13

PIN BURR OF .005 MAX. VERTICAL AND .003 MAX. HORIZONTAL PERMITTED AT POST TIPS ON BOTH ENDS.



RECOMMENDED MOUNTING HOLE PATTERN

2

FOR .063 THICK P.C. BOARD

		2.028	51.51
.065	1.65	.700	17.78
.063	1.60	.450	11.43
.060	1.52	.425	10.80
.045	1.14	.312	7.92
.030	0.76	.300	7.62
.015	0.38	.180	4.57
.012	0.30	.175	4.45
.010	0.25	.156	3.96
.008	0.20	.125	3.18
.005	0.13	.078	1.98
.003	0.08	.073	1.85
.001	0.03	.070	1.78
IN	MM	IN	MM
CONVERSION TABLE			

643326-2 SHOWN

PRELIMINARY	12	643326-5
	4	643326-4
	2	643326-3
OBSOLETE	2,4,6,8,10,12	643326-2
	3	643326-1
	POST NUMBER OMITTED	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN N. GANNON 07OCT92	 TE Connectivity			
		CHK R. SWING 07OCT92				
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD R. SPEER 12OCT92	NAME	MTA-156 HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT .045 SQUARE POST, TIN PLATED, 13 POSITION, OMITTED POST		
		PRODUCT SPEC				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[643326-4](#)